




TRANSAMERICA TIRE CO., LTD.
5118 Park Ave., Suite 601, Memphis, TN 38117
www.venompowertires.com
f o d y @Venompowertires
-2025 (3)



VENOM POWER TIRE
BUILT FOR ADVENTURE

Venom Power Tires is dedicated to serving consumers and the automotive aftermarket by introducing products that prioritize unique sizes, quality, safety, and value. Our tires are meticulously crafted for durability, extended tread life, superior performance, and aesthetic appeal. In essence, we manufacture tires tailored to meet the demands and desires of consumers and enthusiasts, rather than imposing our assumptions of what they require. Whether it's for your daily commute or weekend adventures, our tires ensure a safe journey to and from your destination.

Our high-performance passenger car tires promise a refined, comfortable, and quiet highway ride while delivering the performance necessary for spirited driving conditions. Conversely, our off-road tires empower you to venture farther on any terrain, be it dirt, sand, gravel, rocks, rain, mud, or snow.

Venom Power Tires are produced at our esteemed manufacturing plant renowned for crafting some of the world's finest tires. With decades of expertise, our designers and engineers at Venom Power tirelessly strive to develop premium, high-performing tires. This commitment has propelled us to become one of the fastest-growing and most popular tire brands in North America.

VENOM POWER

SWAMPTHING	TERRA HUNTER	TRAIL HUNTER	RAGNAROK GT S	GRAND AM
<i>Xtreme Dirt</i> SWAMPTHING MIT 01	TERRA HUNTER X/T² 09	TRAIL HUNTER R/T 33	RAGNAROK GT S 47	GRAND AM 67
<i>Xtreme Dirt</i> SWAMPTHING AIT 05	TERRA HUNTER X/T 15	TRAIL HUNTER ATX 39	COVERT GRIP	Co ALLSeason
	TERRA HUNTER R/T+ 21	TRAIL HUNTER ATS 41		Van-Co ALLSeason 73
	TERRA HUNTER M/T 27	ICE HUNTER WT S		AT-Co ALLSeason 75
		ICE HUNTER WT S 43		
			COVERT GRIP ASP 55	
			COVERT GRIP CV 63	
			COVERT GRIP H/T 65	

MAXIMUM TRACTION MUD-TERRAIN TIRE

THE SWAMPTHING M/T IS A HIGH-PERFORMANCE MUD-TERRAIN TIRE CRAFTED FOR MAXIMUM TRACTION AND DURABILITY. DESPITE ITS RUGGED APPEARANCE, EVERY ELEMENT OF ITS DESIGN SERVES A FUNCTIONAL PURPOSE. ITS ROBUST EXTERIOR IS SUPPORTED BY CUTTING-EDGE ENGINEERING, ENSURING PEAK PERFORMANCE ON ANY SURFACE. FEATURING AN AGGRESSIVE TREAD PATTERN AND ADVANCED RUBBER COMPOUND, THE SWAMPTHING M/T DELIVERS UNPARALLELED GRIP AND CONTROL, EVEN IN THE TOUGHEST WEATHER CONDITIONS AND MOST CHALLENGING TERRAINS.



SWAMPTHING M/T

Xtreme Dirt SWAMPTHING MIT

MAXIMUM TRACTION MUD-TERRAIN TIRE

Facebook
venompowertires

Instagram
venompowertires

TikTok
venompowertires

YouTube
venompowertires



- A modern, high-traction mud-terrain tire with striking aesthetics complements its ability to conquer rugged terrain.
- Features a robust and durable 3-ply sidewall ideal for lower tire pressures during rock crawling, enhancing traction.
- An aggressive deep dual-sidewall lug design offers an improved biting edge, ensuring continuous forward momentum.



WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
14"	27X8.50R14LT	6PR 95Q	CVPSWMT25	7J	5.5-7.0	26.52	8.58	16.0	BLK	N
15"	30X9.50R15LT	6PR 104Q	CVPSWMT40R	7 1/2J	6.0-8.0	29.52	9.46	19.0	RWL	N
16"	LT265/75R16	10PR 123/120Q	CVPSWMT21	7 1/2J	7.0-9.0	31.65	10.51	19.0	BLK	N
	LT285/75R16	126/123Q	CVPSWMT23	8J	7.5-9.5	32.83	11.26	19.0	BLK	N
17"	LT265/70R17	10PR 123/120Q	CVPSWMT19	8J	7.0-9.0	31.65	10.71	19.0	RWL	N
	LT285/70R17	10PR 126/123Q	CVPSWMT20	8 1/2J	7.5-9.5	32.76	11.50	19.0	RWL	N
	LT315/70R17	10PR 126/123Q	CVPSWMT18	9 1/2J	8.0-10.5	34.41	12.72	21.0	BLK	N
	35X12.50R17LT	12PR 128R	CVPSWMT01	10J	8.0-10.5	34.52	12.50	21.0	BLK	N
	37X12.50R17LT	8PR 124Q	CVPSWMT28R	10J	8.0-10.5	36.52	12.50	21.0	RWL	N
	37X12.50R17LT	10PR 128Q	CVPSWMT29R	10J	8.0-10.5	36.52	12.50	21.0	RWL	N
	37X13.50R17LT	10PR 128Q	CVPSWMT17	11J	9.0-11.5	36.52	13.58	21.0	BLK	N
18"	40x13.50R17LT	8PR 128Q	CVPSWMT35	11J	9.0-11.5	39.52	13.58	21.0	BLK	N
	35X12.50R18LT	12PR 128R	CVPSWMT02	10J	8.5-11.0	34.52	12.50	21.0	BLK	N
	33X12.50R20LT	10PR 114Q	CVPSWMT03	10J	8.5-11.0	32.52	12.50	21.0	BLK	N
	33X12.50R20LT	12PR 119Q	CVPSWMT04	10J	8.5-11.0	32.52	12.50	21.0	BLK	N
	35X12.50R20LT	10PR 121Q	CVPSWMT05	10J	8.5-11.0	34.52	12.50	21.0	BLK	N
	35X12.50R20LT	12PR 125Q	CVPSWMT06	10J	8.5-11.0	34.52	12.50	21.0	BLK	N
	35X15.50R20LT	12PR 127Q	CVPSWMT37R	12 1/2J	11.0-14.0	34.52	15.54	21.0	RWL	N
20"	38X13.50R20LT	10PR 128Q	CVPSWMT24	11J	9.5-12.0	37.52	13.58	21.0	BLK	N
	40x13.50R20LT	10PR 128Q	CVPSWMT26	11J	9.0-11.5	39.52	13.58	21.0	BLK	N
	33X12.50R22LT	10PR 109Q	CVPSWMT09	10J	10.0-12.0	32.52	12.45	21.0	BLK	N
	33X12.50R22LT	12PR 114Q	CVPSWMT10	10J	10.0-12.0	32.52	12.45	21.0	BLK	N
	33X13.50R22LT	12PR 116Q	CVPSWMT30	12J	11.5-12.5	32.52	13.58	21.0	BLK	N
	35X12.50R22LT	10PR 117Q	CVPSWMT11	10J	8.5-11.0	34.52	12.50	21.0	BLK	N
	35X12.50R22LT	12PR 121Q	CVPSWMT12	10J	8.5-11.0	34.52	12.50	21.0	BLK	N
22"	35X15.50R22LT	12PR 123Q	CVPSWMT38	13J	12.5-14.5	34.52	15.43	21.0	BLK	N
	37X12.50R26LT	12PR 117Q	CVPSWMT16	10J	9.5-11.5	36.52	12.50	21.0	BLK	N
	38X15.50R26LT	12PR 126P	CVPSWMT34	14J	13.5-14.5	37.52	15.5	21.0	BLK	N
26"	42X16.50R30LT	10PR 126Q	CVPSWMT14	15J	14.5-16.0	41.54	16.57	21.0	BLK	N
	44X16.50R30LT	10PR 128Q	CVPSWMT15	15J	14.0-16.0	43.50	16.57	21.0	BLK	N



+ Every effort has been made to verify the accuracy of the listed specifications. Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.

MAXIMUM TRACTION ALL-TERRAIN TIRE

DRAWING ON OUR EXPERTISE IN ALL-TERRAIN TIRE DESIGN, HONED THROUGH THE DEVELOPMENT OF THE TRAIL HUNTER ATX AND TERRA HUNTER X/T, WE'VE CRAFTED OUR TOP-PERFORMING SWAMPTHING A/T TIRE. DESIGNED AS A MAXIMUM TRACTION ALL-TERRAIN TIRE WITH A UNIQUE TREAD PATTERN THAT REDUCES ROAD NOISE ON PAVED SURFACES WHILE ENSURING STABILITY OFF-ROAD.



SWAMPTHING A/T



- Facebook
venompowertires
- Instagram
venompowertires
- TikTok
venompowertires
- YouTube
venompowertires



- Designed as a max traction all-terrain tire with a unique tread pattern that tames road noise on paved surfaces while delivering surefootedness off-road.
- Aggressive dual-sidewall lug design provides enhanced biting edge performance.
- Available in 12-ply design for vehicles requiring higher load ratings.
- 55,000 miles Limited Treadwear Warranty (22-inch sizes and smaller)

WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
15"	205/70R15	100H XL	TVPSWAT69	6J	5.0-7.0	26.34	8.23	13.6	BLK	Y
	215/70R16	100T	TVPSWAT66	6 1/2J	5.5-7.0	27.87	8.70	13.6	BLK	Y
16"	LT305/70R16	12PR 128/125R	TVPSWAT51	9J	8.0-10.0	32.83	12.24	16.0	RWL	N
	LT315/75R16	10PR 127/124R	TVPSWAT52	8 1/2J	8.0-10.5	34.57	12.32	16.0	RWL	N
17"	LT265/70R17	10PR 121/118Q	TVPSWAT55	8J	7.0-9.0	31.65	10.71	16.0	RWL	Y
	LT285/70R17	10PR 126/123Q	TVPSWAT56	8 1/2J	7.5-9.5	32.76	11.50	16.0	RWL	N
	LT295/70R17	10PR 128/125R	TVPSWAT50	8 1/2J	7.5-10.0	33.31	11.77	16.0	BLK	N
	LT305/70R17	10PR 125/122R	TVPSWAT53	9J	8.0-10.0	33.86	12.24	16.0	RWL	N
	LT315/70R17	10PR 126/123R	TVPSWAT47	9 1/2J	8.0-10.5	34.41	12.72	16.0	BLK	N
	35X11.50R17LT	10PR 128Q	TVPSWAT60	9J	7.5-10.0	34.52	11.42	16.0	RWL	N
	35X12.50R17LT	10PR 125Q	TVPSWAT58	10J	8.0-10.5	34.52	12.50	17.0	BLK	N
	37X12.50R17LT	12PR 128Q	TVPSWAT34	10J	8.0-10.5	36.52	12.50	17.0	BLK	N
18"	37X13.50R17LT	10PR 128Q	TVPSWAT35	11J	9.0-11.5	36.52	13.58	17.0	BLK	N
	37X11.50R18LT	10PR 128Q	TVPSWAT65R	9J	7.5-10.0	36.52	11.42	17.0	RWL	N
	37X12.50R18LT	12PR128Q	TVPSWAT38	10J	8.0-10.5	36.52	12.50	17.0	BLK	N
20"	37X13.50R18LT	12PR128Q	TVPSWAT39	11J	9.5-12.0	36.52	13.58	17.0	BLK	N
	265/50R20	111H XL	TVPSWAT48	8 1/2J	7.5-9.5	30.47	10.91	13.6	BLK	Y
	LT275/55R20	10PR 120/117Q	TVPSWAT57	8 1/2J	8.0-9.5	31.89	11.18	16.0	BLK	Y
	LT285/55R20	10PR 122/119Q	CVPSWAT19	9J	8.5-10.0	32.36	11.69	16.0	BLK	N
	LT285/65R20	10PR 127/124Q	TVPSWAT62R	8 1/2J	8.5-10.0	34.57	11.50	16.0	RWL	N
	LT295/65R20	10PR129/126R	TVPSWAT43	8 1/2J	8.5-10.5	35.12	11.77	16.0	BLK	N
	33X11.50R20LT	10PR 118Q	CVPSWAT20	9J	8.0-10.5	32.52	11.42	16.0	BLK	N
	33X12.50R20LT	10PR 114Q	CVPSWAT22	10J	8.5-11.0	32.52	12.50	17.0	BLK	N
	33X12.50R20LT	12PR 119Q	CVPSWAT23	10J	8.5-11.0	32.52	12.50	17.0	BLK	N
	35X11.50R20LT	10PR 124Q	TVPSWAT63R	9J	8.0-10.5	34.52	11.42	16.0	RWL	N
22"	35X12.50R20LT	10PR121Q	CVPSWAT25	10J	8.5-11.0	34.52	12.50	17.0	BLK	N
	35X12.50R20LT	12PR125Q	CVPSWAT26	10J	8.5-11.0	34.52	12.50	17.0	BLK	N
	HL275/50R22	116H XL	TVPSWAT68	8 1/2J	7.5-9.5	32.87	11.18	13.6	BLK	Y
	LT285/55R22	10PR 124/121S	TVPSWAT59	9J	8.5-10.0	34.37	11.69	16.0	BLK	N
	33X12.50R22LT	10PR 109Q	CVPSWAT28	10J	10.0-12.0	32.52	12.45	17.0	BLK	N
	33X12.50R22LT	12PR 114Q	CVPSWAT29	10J	10.0-12.0	32.52	12.45	17.0	BLK	N
24"	35X12.50R22LT	10PR 117Q	CVPSWAT31	10J	8.5-11.0	34.52	12.50	17.0	BLK	N
	35X12.50R22LT	12PR 121Q	CVPSWAT32	10J	8.5-11.0	34.52	12.50	17.0	BLK	N
	35X12.50R24LT	12PR 116Q	TVPSWAT46	10 1/2J	10.0-12.0	34.52	12.45	17.0	BLK	N
	35X13.50R24LT	12PR 116Q	TVPSWAT54	12J	11.5-13.5	34.52	13.44	17.0	BLK	N

+ Every effort has been made to verify the accuracy of the listed specifications. Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.



ADVANCED ON- AND OFF-ROAD ALL-TERRAIN TIRE

THE VENOM POWER TERRA HUNTER X/T 2 BUILDS ON THE SUCCESS OF ITS PREDECESSOR, OFFERING A NEXT-LEVEL ALL-TERRAIN TIRE EXPERIENCE. THIS TIRE COMBINES EXCEPTIONAL ON-ROAD COMFORT, SUPERIOR TRACTION, AND OFF-ROAD VERSATILITY FOR ALL YOUR DRIVING ADVENTURES.

THE TERRA HUNTER X/T 2 IS YOUR TRUSTED COMPANION, NO MATTER THE ROAD AHEAD. COMMUTE CONFIDENTLY, NAVIGATE HIGHWAYS EFFORTLESSLY, AND EXPLORE OFF-ROAD WITH PEACE OF MIND. THIS TIRE IS ENGINEERED TO PROVIDE THE PERFECT BLEND OF COMFORT, SAFETY, AND ALL-TERRAIN CAPABILITY, WHEREVER YOU ROAM.

TERRA HUNTER X/T 2



TERRA HUNTER X/T²

ADVANCED ON- AND OFF-ROAD ALL-TERRAIN TIRE

Facebook
venompowertires

Instagram
venompowertires

TikTok
venompowertires

YouTube
venompowertires



WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
15"	205/65R15	99H XL	VPXT241R	6J	5.5-7.5	25.47	8.23	12.2	RWL	N
	225/75R15	106TXL	VPXT242R	6J	6.0-7.5	28.31	8.78	12.2	RWL	Y
	235/75R15	109T XL	VPXT243R	6 1/2J	6.0-8.0	28.86	9.3	12.2	RWL	Y
	LT215/75R15	8PR 106/103R	VPXT244R	6J	5.5-7.0	27.68	8.50	15.1	RWL	Y
	LT235/75R15	6PR 104/101S	VPXT218R	6 1/2J	6.0-8.0	28.86	9.25	15.1	RWL	Y
	30X9.50R15LT	6PR 104S	VPXT245R	7 1/2J	6.0-8.0	29.52	9.46	15.1	RWL	Y
	31X10.50R15LT	6PR 109S	VPXT215R	8 1/2J	7.0-9.0	30.52	10.54	15.1	RWL	Y
	32X11.50R15LT	6PR 113R	VPXT265R	9J	7.5-10.0	31.52	11.42	15.1	RWL	Y
	33X12.50R15LT	6PR 108R	VPXT266R	10J	8.0-10.5	32.52	12.50	15.1	RWL	Y
	35X12.50R15LT	6PR 113R	VPXT268R	10J	8.0-10.5	34.52	12.50	15.1	RWL	N
16"	215/65R16	102H XL	VPXT239R	6 1/2J	6.0-7.5	27.01	8.70	12.2	RWL	Y
	225/75R16C	10PR 121/120R	VPXT246	6J	6.0-7.0	29.29	8.8	15.1	BLK	Y
	225/75R16C	12PR 122/121R	VPXT275	6J	6.0-7.0	29.29	8.78	15.1	BLK	Y
	235/65R16C	10PR 121/119R	VPXT247	7J	6.5-7.5	28.03	9.5	15.1	BLK	Y
	235/65R16C	12PR 122/120R	VPXT276	7J	6.5-7.5	28.03	9.45	15.1	BLK	Y
	235/70R16	109T XL	VPXT248R	7J	6.0-8.0	28.98	9.4	12.2	RWL	Y
	245/70R16	111T XL	VPXT205	7J	6.5-8.0	29.53	9.76	12.2	BLK	Y
	245/70R16	111T XL	VPXT205R	7J	6.5-8.0	29.53	9.76	12.2	RWL	Y
	245/75R16	115 TXL	VPXT249R	7J	6.5-8.0	30.47	9.76	12.2	RWL	Y
	255/70R16	111S	VPXT236	7 1/2J	6.5-8.5	30.08	10.24	12.2	BLK	Y
	255/70R16	111S	VPXT236R	7 1/2J	6.5-8.5	30.08	10.24	12.2	RWL	Y
	265/70R16	112T	VPXT209	8J	7.0-9.0	30.63	10.71	12.2	BLK	Y

- **Enhanced Comfort, Performance, and Lower Noise:** The Terra Hunter X/T 2 features a specially formulated compound and an optimized tread design, ensuring a quieter ride without compromising grip, handling, or durability. The result is a smoother drive whether you're on the highway or off the beaten path.
- **Superior Braking and Safety:** With advanced tread design and construction, the X/T 2 provides excellent traction in dry, wet, and winter conditions. This leads to shorter stopping distances and greater confidence behind the wheel, ensuring your safety across diverse terrains.
- **Sharper Handling with Stronger Shoulder Blocks:** The reinforced shoulder block design offers improved support during cornering and off-road maneuvers, enhancing overall vehicle control and responsiveness. Navigate sharp turns and rough trails with ease and precision.
- **Optimal Wet Performance with Reduced Void Ratio:** The lower void ratio maximizes rubber contact with the road, delivering superior grip and traction in wet conditions. This design ensures optimal performance during heavy rains and on slippery surfaces.

- **Exceptional Winter Capability with 3PMSF Certification:** The X/T 2 meets the Three-Peak Mountain Snowflake (3PMSF) certification for severe snow service, even in larger tire sizes. Experience exceptional winter performance and safety, no matter the size of your tire.
- **Unified Shoulder and Sidewall Design:** Inspired from feedback from enthusiasts who pushed their Terra Hunter X/Ts to the limit, the X/T 2 features a seamless shoulder and sidewall construction. This design improves handling and stress distribution, providing durability and stability during intense off-road adventures.





WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
16"	265/70R16	112T	VPXT209R	8J	7.0-9.0	30.63	10.71	12.2	RWL	Y
	265/75R16	116T	VPXT211	7 1/2J	7.0-9.0	31.65	10.51	12.2	BLK	Y
	265/75R16	116T	VPXT211R	7 1/2J	7.0-9.0	31.65	10.51	12.2	RWL	Y
	LT215/85R16	10PR 115/112R	VPXT250R	6J	5.5-7.0	30.39	8.50	15.1	RWL	Y
	LT225/75R16	10PR 115/112S	VPXT217R	6J	6.0-7.5	28.31	8.78	15.1	RWL	Y
	LT235/65R16	10PR 120/116S	VPXT220R	6 1/2J	6.0-7.5	31.73	9.25	15.1	RWL	Y
	LT245/75R16	10PR 120/116Q	VPXT223	7J	6.5-8.0	30.47	9.76	15.1	BLK	Y
	LT245/75R16	10PR 120/116Q	VPXT223R	7J	6.5-8.0	30.47	9.76	15.1	RWL	Y
	LT255/85R16	6PR 112/109S	VPXT251R	7J	6.5-8.0	33.07	10.04	15.1	RWL	Y
	LT265/75R16	10PR 123/120Q	VPXT228	7 1/2J	7.0-9.0	31.65	10.51	15.1	BLK	Y
	LT265/75R16	10PR 123/120Q	VPXT228R	7 1/2J	7.0-9.0	31.65	10.51	15.1	RWL	Y
	LT285/75R16	10PR 126/123Q	VPXT235	8J	7.5-9.5	32.83	11.26	15.1	BLK	Y
	LT285/75R16	10PR 126/123Q	VPXT235R	8J	7.5-9.5	32.83	11.26	15.1	RWL	Y
17"	235/75R17	109T	VPXT252R	6 1/2J	6.0-8.0	30.87	9.3	12.2	RWL	Y
	245/65R17	111T XL	VPXT204	7J	7.0-8.5	29.53	9.76	12.2	BLK	Y
	245/65R17	111T XL	VPXT204R	7J	7.0-8.5	29.53	9.76	12.2	RWL	Y
	245/70R17	114T XL	VPXT253R	7J	6.5-8.0	30.55	9.76	12.2	RWL	Y
	255/65R17	114T XL	VPXT254R	7 1/2J	7.0-9.0	30.08	10.2	12.2	RWL	Y
	255/70R17	112T	VPXT255R	7 1/2J	6.5-8.5	31.10	10.2	12.2	RWL	Y
	265/65R17	112T	VPXT207	8J	7.5-9.5	30.55	10.71	12.2	BLK	Y
	265/65R17	112T	VPXT207R	8J	7.5-9.5	30.55	10.71	12.2	RWL	Y
	265/70R17	115S	VPXT210	8J	7.0-9.0	31.65	10.71	12.2	BLK	Y
	265/70R17	115S	VPXT210R	8J	7.0-9.0	31.65	10.71	12.2	RWL	Y
	285/70R17	116T	VPXT263R	8 1/2J	7.5-9.5	32.76	11.50	12.2	RWL	Y
	LT235/80R17	10PR 120/117S	VPXT219	6 1/2J	6.0-8.0	31.81	9.25	15.1	BLK	Y
	LT235/80R17	10PR 120/117S	VPXT219R	6 1/2J	6.0-8.0	31.81	9.25	15.1	RWL	Y
	LT245/70R17	10PR 119/116S	VPXT221	7J	6.5-8.0	30.55	9.76	15.1	BLK	Y
	LT245/70R17	10PR 119/116S	VPXT221R	7J	6.5-8.0	30.55	9.76	15.1	RWL	Y
	LT245/70R17	12PR 123/120Q	VPXT222	7J	6.5-8.0	30.55	9.76	15.1	BLK	Y
	LT245/75R17	10PR 121/118S	VPXT224	7J	6.5-8.0	31.5	9.76	15.1	BLK	Y
	LT245/75R17	10PR 121/118S	VPXT224R	7J	6.5-8.0	31.50	9.76	15.1	RWL	Y
	LT265/65R17	10PR 120/117S	VPXT225	8J	8.0-9.5	30.55	10.71	15.1	BLK	Y
	LT265/65R17	10PR 120/117S	VPXT225R	8J	8.0-9.5	30.55	10.71	15.1	RWL	Y
	LT265/70R17	10PR 123/120Q	VPXT226	8J	7.0-9.0	31.65	10.71	15.1	BLK	Y
	LT265/70R17	10PR 123/120Q	VPXT226R	8J	7.0-9.0	31.65	10.71	15.1	RWL	Y
	LT275/70R17	6PR 114/110S	VPXT256R	8J	7.0-9.0	32.20	10.98	15.1	RWL	Y
	LT285/70R17	10PR 126/123Q	VPXT233	8 1/2J	7.5-9.5	32.76	11.5	15.1	BLK	Y
	LT285/70R17	6PR 116/113Q	VPXT234	8 1/2J	7.5-9.5	32.76	11.5	15.1	BLK	Y
	LT285/70R17	6PR 116/113Q	VPXT234R	8 1/2J	7.5-9.5	32.76	11.50	15.1	RWL	Y
	LT285/70R17	10PR 126/123Q	VPXT233R	8 1/2J	7.5-9.5	32.76	11.50	15.1	RWL	Y
	LT285/75R17	10PR 128/125S	VPXT270R	8J	7.5-9.5	33.86	11.26	15.1	RWL	Y

WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
17"	35X10.50R17LT	10PR 121R	VPXT216	8 1/2J	7.0-9.0	34.52	10.54	15.1	BLK	Y
	35X10.50R17LT	10PR 121R	VPXT216R	8 1/2J	7.0-9.0	34.52	10.54	15.1	RWL	Y
18"	235/60R18	107H XL	VPXT202	7J	6.5-8.5	29.09	9.45	12.2	BLK	Y
	245/60R18	109H XL	VPXT203	7J	7.0-8.5	29.57	9.76	12.2	BLK	Y
	255/70R18	113T	VPXT257R	7 1/2J	6.5-8.5	32.09	10.2	12.2	RWL	Y
	265/60R18	114T XL	VPXT206	8J	7.5-9.5	30.51	10.71	12.2	BLK	Y
	265/60R18	114T XL	VPXT206R	8J	7.5-9.5	30.51	10.71	12.2	RWL	Y
	265/65R18	116T XL	VPXT208	8J	7.5-9.5	31.54	10.71	12.2	BLK	Y
	265/65R18	116T XL	VPXT208R	8J	7.5-9.5	31.54	10.71	12.2	RWL	Y
	275/65R18	116T	VPXT214	8J	7.5-9.5	32.09	10.98	12.2	BLK	Y
	275/65R18	116T	VPXT214R	8J	7.5-9.5	32.09	10.98	12.2	RWL	Y
	285/65R18	116T	VPXT262R	8 1/2J	8.0-10	32.56	11.5	12.2	RWL	Y
	LT265/65R18	10PR 122/119R	VPXT258R	8J	8.0-9.5	31.54	10.71	15.1	RWL	Y
	LT265/70R18	10PR 124/121S	VPXT227	8J	7.0-9.0	32.64	10.71	15.1	BLK	Y
	LT265/70R18	10PR 124/121S	VPXT227R	8J	7.0-9.0	32.64	10.71	15.1	RWL	Y
	LT275/70R18	10PR 125/122S	VPXT231	8J	7.0-9.0	33.19	10.98	15.1	BLK	Y
	LT275/70R18	10PR 125/122S	VPXT231R	8J	7.0-9.0	33.19	10.98	15.1	RWL	Y
	LT285/65R18	10PR 125/122R	VPXT232	8 1/2J	8.5-10.0	32.56	11.5	15.1	BLK	Y
	LT285/65R18	10PR 125/122R	VPXT232R	8 1/2J	8.5-10.0	32.56	11.50	15.1	RWL	Y
	LT285/70R18	10PR 127/124R	VPXT237	8 1/2J	7.5-9.5	33.74	11.5	15.1	BLK	Y
	LT285/70R18	10PR 127/124R	VPXT238	8 1/2J	7.5-9.5	33.74	11.5	15.1	BLK	Y
	LT285/70R18	10PR 127/124R	VPXT238R	8 1/2J	7.5-9.5	33.74	11.50	15.1	RWL	Y
	LT325/65R18	8PR 121/118T	VPXT273R	9 1/2J	9.5-11.5	34.61	13.03	15.1	RWL	Y
	35X11.50R18LT	6PR 117S	VPXT267R	9J	7.5-10.0	34.52	11.42	15.1	RWL	Y
	265/50R20	111T XL	VPXT260R	8 1/2J	7.5-9.5	30.47	10.91	12.2	RWL	Y
20"	275/55R20	117T XL	VPXT212	8 1/2J	7.5-9.5	31.89	11.18	12.2	BLK	Y
	275/60R20	115T	VPXT213	8J	7.5-9.5	32.99	10.98	12.2	BLK	Y
	275/60R20	115T	VPXT213R	8J	7.5-9.5	32.99	10.98	12.2	RWL	Y
	285/55R20	116T XL	VPXT261R	9	8.0-10.0	32.36	11.69	12.2	RWL	N
	305/50R20	120T XL	VPXT264	9 1/2J	8.5-11.0	32.05	12.44	12.2	BLK	Y
	305/55R20	116S	VPXT274R	9 1/2J	8.5-11.0	33.23	12.44	12.2	RWL	N
	LT275/60R20	10PR 123/120R	VPXT229	8J	8.0-9.5	32.99	10.98	15.1	BLK	Y
	LT275/60R20	10PR 123/120R	VPXT229R	8J	8.0-9.5	32.99	10.98	15.1	RWL	Y
	LT275/65R20	10PR 126/123S	VPXT230	8J	8.0-9.5	34.09	10.98	15.1	BLK	Y
	LT275/65R20	10PR 126/123S	VPXT230R	8J	8.0-9.5	34.09	10.98	15.1	RWL	Y
	LT325/60R20	10PR 126/123S	VPXT272	9 1/2J	9.5-11.5	35.35	13.03	15.1	BLK	Y
	37X12.50R20LT	10PR 126R	VPXT269	10J	8.5-11.0	36.52	12.50	15.1	BLK	Y
	LT325/50R22	12PR 127R	VPXT271	10J	9.5-11.5	34.84	13.23	15.1	BLK	N

✦ Every effort has been made to verify the accuracy of the listed specifications. Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.





ON- AND OFF-ROAD ALL-TERRAIN TIRE

EXPERIENCE THE ULTIMATE BLEND OF HIGHWAY COMFORT AND OFF-ROAD PROWESS WITH THE TERRA HUNTER X/T, METICULOUSLY ENGINEERED TO PROVIDE UNRIVALED PERFORMANCE FOR YOUR DAILY COMMUTE AND WEEKEND ADVENTURES. WHETHER NAVIGATING CITY STREETS OR CONQUERING RUGGED TRAILS, THIS TIRE ENSURES YOU CONFIDENTLY TREAD ACROSS DIVERSE TERRAINS WITH EASE AND ASSURANCE. ELEVATE YOUR DRIVING EXPERIENCE WITH THE TERRA HUNTER X/T, DESIGNED TO DELIVER UNPARALLELED VERSATILITY AND PERFORMANCE WHEREVER THE ROAD MAY LEAD.

TERRA HUNTER X/T



4 YEARS WARRANTY

3PLY SELECTED SIZES

50K WARRANTY



- Facebook venompowertires
- Instagram venompowertires
- TikTok venompowertires
- YouTube venompowertires



- Advanced all-terrain tread compound that delivers extended tread life and confident on/off-road traction.
- Deep, multi-functional grooves and sipes bite into any surface, for exceptional performance in all conditions.
- Stepped shoulder lugs enhance grip and conquer rocky paths with ease.
- Mud and stone ejectors maintain traction by efficiently shedding mud and preventing stone drilling.
- Wider contact patch optimizes handling stability for both on-road comfort and off-road control.
- Rugged 3D sidewall lugs combine aggressive aesthetics with superior off-road performance.
- Available in a wide range of sizes (15" - 28" wheel diameters, up to 40" overall diameter), Terra Hunter X/T is your perfect adventure companion.

WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
15"	LT235/75R15	6PR 104/101S	TVPXT61	6 1/2J	6.0-8.0	28.86	9.25	14.5	BLK	N
	31X10.50R15LT	6PR 109S	TVPXT60	8 1/2J	7.0-9.0	30.52	10.54	14.5	BLK	N
16"	245/70R16	111T XL	TVPXT64	7J	6.5-8.0	29.53	9.76	12.2	BLK	N
	265/70R16	112T	TVPXT65	8J	7.0-9.0	30.63	10.71	12.2	BLK	N
	265/75R16	116T	TVPXT66	7 1/2J	7.0-9.0	31.65	10.51	12.2	BLK	N
	LT225/75R16	10PR 115/112S	TVPXT62	6J	6.0-7.5	29.29	8.78	15.1	BLK	N
	LT235/85R16	10PR 120/116S	TVPXT63	6 1/2J	6.0-7.5	31.73	9.25	15.1	BLK	N
	LT245/75R16	10PR 120/116Q	TVPXT27	7J	6.5-8.0	30.47	9.76	15.4	BLK	N
	LT265/75R16	10PR 123/120Q	TVPXT28	7 1/2J	7.0-9.0	31.65	10.51	15.4	BLK	N
	LT285/75R16	10PR 126/123Q	TVPXT29	8J	7.5-9.5	32.83	11.26	15.4	BLK	N
	245/65R17	111T XL	TVPXT68	7J	7.0-8.5	29.53	9.76	12.2	BLK	N
	265/65R17	112T	TVPXT71	8J	7.5-9.5	30.55	10.71	12.2	BLK	N
17"	265/70R17	115S	TVPXT31	8J	7.0-9.0	31.65	10.71	12.6	BLK	N
	LT235/80R17	10PR 120/117S	TVPXT67	6 1/2J	6.0-8.0	31.81	9.25	15.1	BLK	N
	LT245/70R17	10PR 119/116S	TVPXT69	7J	6.5-8.0	30.55	9.76	15.1	BLK	N
	LT245/75R17	10PR 121/118S	TVPXT70	7J	6.5-8.0	31.50	9.76	15.1	BLK	N
	LT255/80R17	10PR 121/118R	SVPXT21	7 J	6.5-8.5	33.07	10.04	15.1	BLK	N
	LT265/65R17	10PR 120/117S	TVPXT72	8J	8.0-9.5	30.55	10.71	15.1	BLK	N
	LT265/70R17	10PR 121/118Q	TVPXT30	8J	7.0-9.0	31.65	10.71	15.4	BLK	N
	LT285/70R17	6PR 116/113Q	TVPXT80	8 1/2J	7.5-9.5	32.76	11.50	15.4	BLK	N
	LT285/70R17	10PR 121/118Q	TVPXT32	8 1/2J	7.5-9.5	32.76	11.50	15.4	BLK	N
	33X12.50R17LT	10PR 120R	TVPXT01	10J	8.5-11.0	32.52	12.50	15.1	BLK	N
	35X10.50R17LT	10PR 121R	TVPXT73	8 1/2J	7.0-9.0	34.52	10.54	15.1	BLK	N
	35X12.50R17LT	10PR 121R	TVPXT13	10J	8.0-10.5	34.52	12.50	15.1	BLK	N
	35X12.50R17LT	12PR 124R	TVPXT39	10J	8.0-10.5	34.52	12.50	15.1	BLK	N
	235/60R18	107H XL	TVPXT74	7J	6.5-8.5	29.09	9.45	12.2	BLK	N
18"	245/60R18	109H XL	TVPXT75	7J	7.0-8.5	29.57	9.76	12.2	BLK	N
	265/60R18	114T XL	TVPXT76	8J	7.5-9.5	30.51	10.71	12.2	BLK	N
	265/65R18	116T XL	TVPXT77	8J	7.5-9.5	31.54	10.71	12.2	BLK	N
	275/65R18	116T	TVPXT79	8J	7.5-9.5	32.09	10.98	12.2	BLK	N

✦ Every effort has been made to verify the accuracy of the listed specifications. Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.





WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
18"	LT265/70R18	10PR 124/121S	TVPXT78	8J	7.0-9.0	32.64	10.71	15.1	BLK	N
	LT275/70R18	10PR 125/122S	TVPXT33	8J	7.0-9.0	33.19	10.98	15.4	BLK	N
	LT285/65R18	10PR 125/122R	TVPXT34	8 1/2J	8.5-10.0	32.56	11.50	15.1	BLK	N
	LT285/75R18	10PR 129/126R	SVPXT13	8J	7.5-9.5	34.84	11.26	15.1	BLK	N
	LT295/70R18	10PR 129/126R	SVPXT14	8 1/2J	7.5-10.0	34.29	11.77	15.1	BLK	N
	33X12.50R18LT	10PR 118R	TVPXT02	10J	8.5-11.0	32.52	12.50	15.1	BLK	N
	33X12.50R18LT	12PR 122R	TVPXT03	10J	8.5-11.0	32.52	12.50	15.1	BLK	N
	35X12.50R18LT	10PR 123R	TVPXT14	10J	8.5-11.0	34.52	12.50	15.1	BLK	N
	35X12.50R18LT	12PR 128R	TVPXT15	10J	8.5-11.0	34.52	12.50	15.1	BLK	N
20"	275/55R20	117T XL	TVPXT35	8 1/2J	7.5-9.5	31.89	11.18	12.6	BLK	N
	275/60R20	115T	TVPXT36	8J	7.5-9.5	32.99	10.98	12.6	BLK	N
	LT265/50R20	10PR 117/114S	TVPXT19	8 1/2J	8.0-9.5	30.47	10.91	15.1	BLK	N
	LT275/55R20	10PR 120/117S	TVPXT20	8 1/2J	8.0-9.5	31.89	11.18	15.1	BLK	N
	LT275/60R20	10PR 123/120R	TVPXT37	8J	8.0-9.5	32.99	10.98	15.4	BLK	N
	LT275/65R20	10PR 126/123S	TVPXT38	8J	8.0-9.5	34.09	10.98	15.4	BLK	N
	LT285/50R20	10PR 119/116S	TVPXT21	9J	8.5-10.0	31.26	11.69	15.1	BLK	N
	LT285/55R20	10PR 122/119S	TVPXT12	9J	8.5-10.0	32.36	11.69	15.1	BLK	N
	LT285/60R20	10PR 125/122R	SVPXT22	8 1/2J	8.5-10.0	33.46	11.50	15.1	BLK	N
	LT295/55R20	10PR 123/120R	SVPXT16	9 1/2J	8.5-10.5	32.76	12.17	15.1	BLK	N
	LT295/60R20	10PR 126/123R	SVPXT17	8 1/2J	8.5-10.5	33.94	11.77	15.1	BLK	N
	LT305/55R20	10PR 121/118Q	TVPXT41	9 1/2J	9.0-11.0	33.23	12.44	15.1	BLK	N
	LT305/55R20	12PR 125/122Q	TVPXT42	9 1/2J	9.0-11.0	33.23	12.44	15.1	BLK	N
	33X11.50R20LT	10PR 118Q	SVPXT19	9J	8.0-10.5	32.52	11.42	15.1	BLK	N
	33X12.50R20LT	10PR 114R	TVPXT04	10J	8.5-11.0	32.52	12.50	15.1	BLK	N
	33X12.50R20LT	10PR 114R	TVPXT04R	10J	8.5-11.0	32.52	12.50	15.1	RWL	N
	33X12.50R20LT	12PR 119R	TVPXT05	10J	8.5-11.0	32.52	12.50	15.1	BLK	N
	35X12.50R20LT	10PR 121R	TVPXT08	10J	8.5-11.0	34.52	12.50	15.1	BLK	N
	35X12.50R20LT	10PR 121R	TVPXT08R	10J	8.5-11.0	34.52	12.50	15.1	RWL	N
	35X12.50R20LT	12PR 125R	TVPXT09	10J	8.5-11.0	34.52	12.50	15.1	BLK	N
	37X13.50R20LT	10PR 127Q	TVPXT16	11J	9.5-12.0	36.52	13.58	15.1	BLK	N
	37X13.50R20LT	12PR 128Q	TVPXT17	11J	9.5-12.0	36.52	13.58	15.1	BLK	N

WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
22"	285/45R22	114T XL	TVPXT18	9 1/2J	9.0-10.5	32.09	11.22	12.2	BLK	N
	305/40R22	114H XL	TVPXT22	11J	10.0-12.0	31.61	12.32	12.2	BLK	N
	305/45R22	118S XL	TVPXT81	10J	9.5-11.5	32.80	11.93	12.5	BLK	N
	LT285/50R22	10PR 121/118R	SVPXT20	9J	8.5-10.0	33.27	11.69	15.1	BLK	N
	33X12.50R22LT	10PR 109R	TVPXT06	10J	10.0-12.0	32.52	12.45	15.1	BLK	N
	33X12.50R22LT	10PR 109R	TVPXT06R	10J	10.0-12.0	32.52	12.45	15.1	RWL	N
	33X12.50R22LT	12PR 114Q	TVPXT07	10J	10.0-12.0	32.52	12.45	15.1	BLK	N
	33X14.50R22LT	10PR 111Q	CVPXT07	13J	12.5-14.0	32.52	14.46	15.1	BLK	N
	35X12.50R22LT	10PR 117R	TVPXT10	10J	8.5-11.0	34.52	12.50	15.1	BLK	N
	35X12.50R22LT	12PR 121Q	TVPXT11	10J	8.5-11.0	34.52	12.50	15.1	BLK	N
	35X12.50R22LT	10PR 117R	TVPXT10R	10J	8.5-11.0	34.52	12.50	15.1	RWL	N
	35X13.50R22LT	10PR 120Q	CVPXT01	11J	10.5-12.0	34.52	13.58	15.1	BLK	N
	35X15.50R22LT	12PR 123Q	CVPXT10	13J	12.5-14.5	34.52	15.43	15.1	BLK	N
	37X13.50R22LT	10PR 123Q	TVPXT26	11J	9.5-12.0	36.52	13.58	15.1	BLK	N
	37X13.50R22LT	12PR 128Q	TVPXT23	11J	9.5-12.0	36.52	13.58	15.1	BLK	N
24"	285/40R24	112H XL	CVPXT04	10J	9.5-11.0	32.99	11.42	12.2	BLK	N
	33X13.50R24LT	12PR 113Q	CVPXT05N	12J	11.5-12.5	32.52	13.78	15.1	BLK	N
	33X14.50R24LT	12PR 118Q	CVPXT08N	13J	12.5-14.0	32.52	13.44	15.1	BLK	N
	35X13.50R24LT	12PR 116Q	CVPXT02	12J	11.5-13.5	34.52	13.44	15.1	BLK	N
	35X15.50R24LT	10PR 118Q	CVPXT11N	13 1/2J	13.0-15.5	34.52	15.52	15.1	BLK	N
	37X13.50R24LT	10PR 120Q	TVPXT50	11J	9.5-12.0	36.52	13.58	15.1	BLK	N
	37X13.50R24LT	12PR 124Q	TVPXT24	11J	9.5-12.0	36.52	13.58	15.1	BLK	N
	305/30R26	109V XL	CVPXT22	11J	10.5-11.5	33.23	12.32	12.6	BLK	N
26"	33X13.50R26LT	10PR 107Q	CVPXT06	12 1/2J	12.0-13.0	32.52	13.58	15.1	BLK	N
	33X14.50R26LT	10PR 108Q	CVPXT09	13J	12.5-14.0	32.52	14.53	15.1	BLK	N
	35X13.50R26LT	12PR 122Q	CVPXT03N	12J	11.5-12.5	34.52	13.58	15.1	BLK	N
	35X15.50R26LT	12PR 120Q	CVPXT12N	14J	13.5-14.5	34.52	15.51	15.1	BLK	N
	37X13.50R26LT	10PR 114Q	TVPXT51	11J	10.5-13.0	36.52	13.44	15.1	BLK	N
	37X13.50R26LT	12PR 117Q	TVPXT25	11J	10.5-13.0	36.52	13.44	15.1	BLK	N
28"	40X15.50R28LT	10PR 126P	TVPXT40	13 1/2J	13.0-14.0	39.52	15.54	19.5	BLK	N

✦ Every effort has been made to verify the accuracy of the listed specifications. Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.




ON- AND OFF-ROAD RUGGED-TERRAIN TIRE

THE TERRA HUNTER R/T+ IS A TIRE THAT DEFIES LIMITS BY BLENDING RUGGED OFF-ROAD PERFORMANCE WITH HIGHWAY COMFORT. ENGINEERED TO HANDLE THE TOUGHEST OFF-ROAD CHALLENGES WHILE MAINTAINING SMOOTH, UNCOMPROMISED PERFORMANCE ON THE ROAD, THIS TIRE EXEMPLIFIES RESILIENCE AND RELIABILITY IN EVERY MILE TRAVELED, EMPOWERING YOU TO PUSH BOUNDARIES WITHOUT HESITATION. EMBRACE ADVENTURE, DOMINATE CHALLENGES, AND MAKE A STATEMENT WITH THE TERRA HUNTER R/T+, THE ULTIMATE TIRE FOR THE ADVENTUROUS SPIRIT.

TERRA HUNTER R/T+

TERRA HUNTER R/T+

ON- AND OFF-ROAD RUGGED-TERRAIN TIRE



- The optimized tread design with a high void-to-lug ratio digs deep for superior traction in mud, snow, sand, and rocky terrain.
- Deep tread depth delivers extended tread life, all-season grip, and also enhances resistance to hydroplaning, for year-round performance.
- Staggered shoulder lugs provide exceptional bite on challenging terrain, while deep siping throughout the tread enhances grip and braking on wet and winter surfaces.
- Mud and stone ejectors strategically placed between shoulder lug blocks facilitate efficient mud shedding and prevent stone drilling for uninterrupted performance.
- Advanced tread pattern and pitch variation effectively reduce road noise, ensuring a smooth and comfortable highway experience for both drivers and passengers.
- The Terra Hunter R/T+ boasts an aggressive dual sidewall design that offers enhanced off-road traction, sidewall protection, and a customizable look to match your adventurous spirit.



WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
17"	LT235/80R17	10PR 120/117Q	TVPRT30	6 1/2J	6.0-8.0	31.81	9.25	16.0	BLK	N
	LT245/75R17	10PR 121/118Q	TVPRT31	7J	6.5-8.0	31.50	9.76	16.0	BLK	N
	LT265/70R17	10PR 121/118Q	TVPRT01NL	8J	7.0-9.0	31.65	10.71	16.0	BLK	N
	LT285/70R17	10PR 121/118Q	TVPRT02NL	8 1/2J	7.5-9.5	32.76	11.50	16.0	BLK	N
	33X12.50R17LT	10PR 120Q	TVPRT05NL	10J	8.5-11.0	32.52	12.50	17.6	BLK	N
	35X12.50R17LT	10PR 121Q	TVPRT08NL	10J	8.0-10.5	34.52	12.50	17.6	BLK	N
	40X13.50R17LT	8PR 121Q	TVPRT40	11J	9.0-11.5	39.52	13.58	17.6	BLK	N
18"	LT275/65R18	10PR 123/120Q	TVPRT10NL	8J	8.0-9.5	32.09	10.98	16.0	BLK	N
	LT275/70R18	12PR 128/125Q	TVPRT03N	8J	7.0-9.0	33.19	10.98	16.0	BLK	N
	33X12.50R18LT	10PR 118Q	TVPRT06NL	10J	8.5-11.0	32.52	12.50	17.6	BLK	N
	35X12.50R18LT	10PR 123Q	TVPRT09NL	10J	8.5-11.0	34.52	12.50	17.6	BLK	N
20"	275/55R20	11TT XL	TVPRT26	8 1/2J	7.5-9.5	31.89	11.18	13.2	BLK	N
	285/55R20	116T XL	TVPRT27	9J	8.0-10.0	32.36	11.69	13.2	BLK	N
	305/55R20	116R XL	TVPRT28	9 1/2J	8.5-11.0	33.23	12.44	13.2	BLK	N
	LT265/60R20	10PR 121/118Q	TVPRT32	8J	8.0-9.5	32.52	10.71	16.0	BLK	N
	LT275/55R20	10PR 120/117Q	TVPRT11NL	8 1/2J	8.0-9.5	31.89	11.18	16.0	BLK	N
	LT275/65R20	12PR 128/125R	TVPRT12N	8J	8.0-9.5	34.09	10.98	16.0	BLK	N
	LT285/55R20	10PR 122/119S	TVPRT13NL	9J	8.5-10.0	32.36	11.69	16.0	BLK	N
	LT285/65R20	10PR 127/124Q	TVPRT33	8 1/2J	8.5-10.0	34.57	11.50	16.0	BLK	N
	LT305/55R20	10PR 121/118S	TVPRT14NL	9 1/2J	9.0-11.0	33.23	12.44	16.0	BLK	N
	31X12.50R20LT	10PR 118Q	CVPRTO1	10 1/2J	9.5-10.5	30.51	12.52	16.0	BLK	N
	31X13.50R20LT	10PR 121Q	CVPRTO4	11J	10.5-12.0	30.51	13.58	16.0	BLK	N
	33X10.50R20LT	10PR 121Q	TVPRT36	8 1/2J	8.0-9.5	32.52	10.54	17.6	BLK	N
	33X11.50R20LT	10PR 118Q	TVPRT37	9J	8.0-10.5	32.52	11.42	17.6	BLK	N
	33X12.50R20LT	10PR 114Q	TVPRT35N	10J	8.5-11.0	32.52	12.50	17.6	BLK	N

✦ Every effort has been made to verify the accuracy of the listed specifications. Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.





WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
20"	33X12.50R20LT	10PR 114Q	TVPRT35NR	10J	8.5-11.0	32.52	12.50	17.6	RWL	N
	33X12.50R20LT	12PR 119Q	TVPRT15N	10J	8.5-11.0	32.52	12.50	17.6	BLK	N
	33X14.50R20LT	12PR 120Q	CVPRT12	11 1/2J	11.0-12.0	32.52	14.46	18.6	BLK	N
	35X11.50R20LT	10PR 124Q	TVPRT38	9J	8.0-10.5	34.52	11.42	16.0	BLK	N
	35X12.50R20LT	10PR 121Q	TVPRT34N	10J	8.5-11.0	34.52	12.50	17.6	BLK	N
	35X12.50R20LT	10PR 121Q	TVPRT34NR	10J	8.5-11.0	34.52	12.50	17.6	RWL	N
	35X12.50R20LT	12PR 125Q	TVPRT18N	10J	8.5-11.0	34.52	12.50	17.6	BLK	N
	35X13.50R20LT	12PR 126Q	TVPRT39	11J	9.5-12.0	34.52	13.58	17.6	BLK	N
	35X14.50R20LT	12PR 127Q	CVPRT14	11 1/2J	11.0-12.0	34.52	14.46	18.6	BLK	N
	35X15.50R20LT	12PR 127Q	CVPRT16	12 1/2J	11.0-14.0	34.52	15.54	18.6	BLK	N
22"	30S/45R22	118T XL	TVPRT29	10J	9.5-11.5	32.80	11.93	13.2	BLK	N
	31X12.50R22LT	10PR 115Q	CVPRT02	11 1/2J	11.0-12.0	30.51	12.36	16.0	BLK	N
	31X13.50R22LT	10PR 118Q	CVPRT05	12J	11.5-12.5	30.51	13.35	16.0	BLK	N
	33X12.50R22LT	12PR 114Q	TVPRT16N	10J	10.0-12.0	32.52	12.45	17.6	BLK	N
	33X12.50R22LT	12PR 114Q	TVPRT16NR	10J	10.0-12.0	32.52	12.45	17.6	RWL	N
	33X13.50R22LT	12PR 114Q	CVPRT11	11J	10.5-12.0	32.52	13.58	18.6	BLK	N
	33X14.50R22LT	12PR 115Q	CVPRT13	13J	12.5-14.0	32.52	14.46	18.6	BLK	N
	35X12.50R22LT	12PR 121Q	TVPRT20N	10J	8.5-11.0	34.52	12.50	17.6	BLK	N
	35X12.50R22LT	12PR 121Q	TVPRT20NR	10J	8.5-11.0	34.52	12.50	17.6	RWL	N
	35X14.50R22LT	12PR 123Q	CVPRT15	11 1/2J	11.0-12.5	34.52	14.46	18.6	BLK	N
	35X15.50R22LT	12PR 123Q	CVPRT17	13J	12.5-14.5	34.52	15.43	18.6	BLK	N
	37X13.50R22LT	12PR 128Q	TVPRT22N	11J	9.5-12.0	36.52	13.58	17.6	BLK	N
	31X12.50R24LT	10PR 109Q	CVPRT03	11 1/2J	11.0-12.0	30.51	12.36	16.0	BLK	N
	31X13.50R24LT	10PR 111Q	CVPRT06	12 1/2J	12.0-13.0	30.51	13.35	16.0	BLK	N
24"	33X12.50R24LT	12PR 106Q	TVPRT17	11 1/2J	10.5-12.5	32.52	12.60	17.6	BLK	N
	33X13.50R24LT	10PR 109Q	CVPRT18	12J	11.5-12.5	32.52	13.43	18.6	BLK	N
	33X14.50R24LT	10PR 110Q	CVPRT20	13J	12.5-14.0	32.52	14.46	18.6	BLK	N
	35X12.50R24LT	12PR 116Q	TVPRT21	10 1/2J	10.0-12.0	34.52	12.45	17.6	BLK	N
	35X14.50R24LT	10PR 118Q	CVPRT22	13J	12.5-14.0	34.52	14.46	18.6	BLK	N
	35X15.50R24LT	10PR 118Q	CVPRT24	13 1/2J	13.0-15.5	34.52	15.52	18.6	BLK	N

WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
24"	37X13.50R24LT	12PR 124Q	TVPRT23N	11J	9.5-12.0	36.52	13.58	17.6	BLK	N
	37X15.50R24LT	12PR 126Q	CVPRT27	12 1/2J	12.0-13.5	36.52	15.54	18.6	BLK	N
26"	33X12.50R26LT	12PR 110Q	CVPRT62N	11 1/2J	11.0-12.0	32.52	12.50	17.6	BLK	N
	33X13.50R26LT	10PR 107Q	CVPRT19	12 1/2J	12.0-13.0	32.52	13.58	18.6	BLK	N
	33X14.50R26LT	10PR 108Q	CVPRT21	13J	12.5-14.0	32.52	14.46	18.6	BLK	N
	35X12.50R26LT	12PR 119Q	CVPRT63N	11 1/2J	11.0-12.0	34.52	12.50	16.0	BLK	N
	35X14.50R26LT	10PR 117Q	CVPRT23	13J	12.5-14.0	34.52	14.46	18.6	BLK	N
	35X15.50R26LT	10PR 116Q	CVPRT25	14J	13.5-14.5	34.52	15.51	18.6	BLK	N
	37X13.50R26LT	12PR 117Q	TVPRT25N	11J	10.5-13.0	36.52	13.44	17.6	BLK	N
	37X14.50R26LT	12PR 118Q	CVPRT26	12 1/2J	12.0-13.0	36.52	14.46	18.6	BLK	N
	37X15.50R26LT	12PR 118Q	CVPRT28	13 1/2J	13.0-14.0	36.52	15.54	18.6	BLK	N
28"	40X15.50R28LT	10PR 126P	TVPRT42	13 1/2J	13.0-14.0	39.52	15.54	19.5	BLK	N



OFF-ROAD MAXIMUM TRACTION TIRE

THE TERRA HUNTER M/T IS A MAXIMUM TRACTION TIRE FEATURING A TIME-HONORED CLASSIC MUD TREAD DESIGN. ITS ROBUST, BLOCKY TREAD, AND DUAL SIDEWALL LUG DESIGN ALLOW YOU TO CONQUER THE TOUGHEST TERRAIN AND WEATHER CONDITIONS, EFFORTLESSLY NAVIGATING MUD, SNOW, SAND, AND ROCKS WITH EASE. SIMPLY POINT THE WAY, AND THE TERRA HUNTER M/T WILL TAKE YOU THERE.

TERRA HUNTER M/T

TERRA HUNTER M/T

OFF-ROAD MAXIMUM TRACTION TIRE

f Facebook
venompowertires

o Instagram
venompowertires

o TikTok
venompowertires

o YouTube
venompowertires



- Optimized void-to-lug ratio for extreme off-road conditions provides unparalleled traction in mud, snow, sand, and rocky terrain.
- Staggered shoulder lugs offer enhanced biting edge and traction on rocky terrain.
- Deep siping in the tread blocks provides enhanced grip and braking on winter and wet surfaces.
- Mud and stone ejectors positioned between shoulder lug blocks help shed mud and prevent stone drilling.
- The aggressive dual sidewall design of the Terra Hunter M/T not only delivers added off-road traction and sidewall armor but also provides enthusiasts with aesthetic options to indulge their wild side.



WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
17"	LT305/65R17	10PR 121/118Q	TVPMT11	9J	9.0-11.0	32.60	12.24	20.4	BLK	N
	33X12.50R17LT	10PR 120Q	TVPMT38	10J	8.5-11.0	32.52	12.50	20.4	BLK	N
	LT305/60R18	10PR 121/118Q	TVPMT12	9J	9.0-11.0	32.40	12.24	20.4	BLK	N
18"	33X12.50R18LT	10PR 118Q	TVPMT39	10J	8.5-11.0	32.52	12.50	20.4	BLK	N
	LT275/55R20	10PR 120/117Q	TVPMT13	8 1/2J	8.0-9.5	31.89	11.18	18.6	BLK	N
20"	LT285/55R20	10PR 122/119Q	TVPMT37	9J	8.5-10.0	32.36	11.69	18.6	BLK	N
	33X11.50R20LT	10PR 118Q	TVPMT17	9J	8.0-10.5	32.52	11.42	18.6	BLK	N
	33X12.50R20LT	10PR 114Q	TVPMT35	10J	8.5-11.0	32.52	12.50	20.4	BLK	N
	33X12.50R20LT	10PR 114Q	TVPMT35R	10J	8.5-11.0	32.52	12.50	20.4	RWL	N
	33X12.50R20LT	12PR 119Q	TVPMT15	10J	8.5-11.0	32.52	12.50	20.4	BLK	N
	33X13.50R20LT	12PR 120Q	TVPMT40	11J	9.5-12.0	32.52	13.58	20.4	BLK	N
	35X12.50R20LT	10PR 121Q	TVPMT34	10J	8.5-11.0	34.52	12.50	20.4	BLK	N
	35X12.50R20LT	10PR 121Q	TVPMT34R	10J	8.5-11.0	34.52	12.50	20.4	RWL	N
	35X12.50R20LT	12PR 125Q	TVPMT18	10J	8.5-11.0	34.52	12.50	20.4	BLK	N
	35X13.50R20LT	12PR 126Q	TVPMT19	11J	9.5-12.0	34.52	13.58	20.4	BLK	N
	38X15.50R20LT	10PR 128Q	TVPMT41	12 1/2J	11.0-14.0	37.52	15.54	20.4	BLK	N
	40X15.50R20LT	12PR 128Q	TVPMT21	12 1/2J	11.0-14.0	39.52	15.54	20.4	BLK	N
22"	33X12.50R22LT	10PR 109Q	TVPMT16L	10J	10.0-12.0	32.52	12.45	20.4	BLK	N
	33X12.50R22LT	10PR 109Q	TVPMT16LR	10J	10.0-12.0	32.52	12.45	20.4	RWL	N
	33X12.50R22LT	12PR 114Q	TVPMT16	10J	10.0-12.0	32.52	12.45	20.4	BLK	N
	33X13.50R22LT	12PR 116Q	CVPMT22	11J	10.5-12.0	32.52	13.58	20.4	BLK	N
	35X12.50R22LT	10PR 117Q	TVPMT20L	10J	8.5-11.0	34.52	12.50	20.4	BLK	N
	35X12.50R22LT	10PR 117Q	TVPMT20LR	10J	8.5-11.0	34.52	12.50	20.4	RWL	N
	35X12.50R22LT	12PR 121Q	TVPMT20	10J	8.5-11.0	34.52	12.50	20.4	BLK	N
	35X13.50R22LT	12PR 122Q	CVPMT23	11J	10.5-12.0	34.52	13.58	20.4	BLK	N
	40X15.50R22LT	12PR 128Q	TVPMT36	12 1/2J	11.0-14.0	39.52	15.54	20.4	BLK	N





WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
24"	33X13.50R24LT	10PR 109Q	CVPMT25	12J	11.5-12.5	32.52	13.43	20.4	BLK	N
	35X13.50R24LT	12PR 116Q	TVPMT26	12J	11.5-13.5	34.52	13.44	20.4	BLK	N
	38X15.50R24LT	12PR 128P	CVPMT27	12 1/2J	12.5-14.5	37.52	15.43	20.4	BLK	N
	40X15.50R24LT	12PR 128P	TVPMT28	12 1/2J	11.0-14.0	39.52	15.54	20.4	BLK	N
26"	35X13.50R26LT	10PR 118Q	CVPMT29	12J	11.5-12.5	34.52	13.58	20.4	BLK	N
	38X15.50R26LT	12PR 126P	CVPMT30	13 1/2J	13.0-14.0	37.52	15.47	20.4	BLK	N
	40X15.50R26LT	10PR 126P	TVPMT31	12 1/2J	12.5-14.5	39.52	15.43	20.4	BLK	N
28"	40X15.50R28LT	10PR 126P	TVPMT32	13 1/2J	13.0-14.0	39.52	15.54	20.4	BLK	N
	42X15.50R28LT	10PR 128P	TVPMT33	13 1/2J	12.5-14.5	41.52	15.43	20.4	BLK	N

✦ Every effort has been made to verify the accuracy of the listed specifications. Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.



TRAIL HUNTER R/T

ON- AND OFF-ROAD MAX TRACTION RUGGED-TERRAIN TIRE

THE TRAIL HUNTER R/T IS VENOM POWER'S PREMIER HYBRID OFF-ROAD TIRE, ENGINEERED FOR MAXIMUM TRACTION ON DIVERSE TERRAINS. WITH ITS OPTIMIZED DESIGN, DEEP TREAD DEPTH, AND ADVANCED FEATURES, THE TRAIL HUNTER R/T ENSURES MAXIMUM GRIP IN EXTREME CONDITIONS WHILE PROVIDING A SMOOTH AND QUIET RIDE ON THE HIGHWAY, MAKING IT THE IDEAL CHOICE FOR ADVENTURERS SEEKING VERSATILITY AND RELIABILITY ON- AND OFF-ROAD.



TRAIL HUNTER R/T

ON- AND OFF-ROAD MAX TRACTION RUGGED-TERRAIN TIRE

- Facebook
venompowertires
- Instagram
venompowertires
- TikTok
venompowertires
- YouTube
venompowertires



- Optimized void-to-lug ratio ensures unparalleled traction in extreme off-road conditions such as mud, snow, sand, and rocky terrain.
- Deep tread depth provides superior off-road capability, resistance to hydroplaning, and extended tread life.
- Squared shoulder blocks ensure a larger contact patch for improved traction both on- and off-road.
- Dual shoulder block siping enhances handling stability, grip, and braking performance on wet and winter surfaces.
- Mud and stone ejectors between shoulder lug blocks prevent mud buildup and stone drilling.
- Advanced tread pattern and pitch variation reduce road noise for a quieter highway ride, enhancing driver and passenger comfort.
- Aggressive dual sidewall design not only enhances off-road traction and sidewall protection but also offers aesthetic options.
- Available in light truck (LT) sizes ranging from 17 to 22 inches.

ROAD HAZARD

4 YEARS WARRANTY

3PLY SELECTED SIZES

50K WARRANTY

FULL TREAD FULL TREAD DEPTH

WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
16"	LT235/85R16	10PR 120/116Q	CVPTHRT39	6 1/2J	6.0-7.5	31.73	9.25	15.7	BLK	Y
	LT235/85R16	10PR 120/116Q	CVPTHRT39R	6 1/2J	6.0-7.5	31.73	9.25	15.7	RWL	Y
	LT265/75R16	10PR 123/120R	CVPTHRT23	7 1/2J	7.0-9.0	31.65	10.51	15.7	BLK	Y
	LT265/75R16	10PR 123/120R	CVPTHRT23R	7 1/2J	7.0-9.0	31.65	10.51	15.7	RWL	Y
	LT285/75R16	10PR 126/123R	CVPTHRT28	8 J	7.5-9.5	32.83	11.26	15.7	BLK	N
	LT285/75R16	10PR 126/123R	CVPTHRT28R	8 J	7.5-9.5	32.83	11.26	15.7	RWL	N
17"	265/70R17	115S	CVPTHRT29	8 J	7.0-9.0	31.65	10.71	12.2	BLK	Y
	265/70R17	115S	CVPTHRT29R	8 J	7.0-9.0	31.65	10.71	12.2	RWL	Y
	LT265/65R17	10PR 120/117Q	CVPTHRT38	8J	8.0-9.5	30.55	10.71	15.7	BLK	Y
	LT265/65R17	10PR 120/117Q	CVPTHRT38R	8J	8.0-9.5	30.55	10.71	15.7	RWL	Y
	LT265/70R17	10PR 123/120Q	CVPTHRT22	8 J	7.0-9.0	31.65	10.71	15.7	BLK	Y
	LT265/70R17	10PR 123/120Q	CVPTHRT22R	8 J	7.0-9.0	31.65	10.71	15.7	RWL	Y
	LT285/70R17	10PR 126/123Q	CVPTHRT27	8 1/2J	7.5-9.5	32.76	11.50	15.7	BLK	N
	LT285/70R17	10PR 126/123Q	CVPTHRT27R	8 1/2J	7.5-9.5	32.76	11.50	15.7	RWL	N
	33X12.50R17LT	10PR 120Q	CVPTHRT09	10J	8.5-11.0	32.52	12.50	15.7	BLK	N
	33X12.50R17LT	10PR 120Q	CVPTHRT09R	10J	8.5-11.0	32.52	12.50	15.7	RWL	N
	35X12.50R17LT	10PR 125R	CVPTHRT02	10J	8.0-10.5	34.52	12.50	15.7	BLK	N
	35X12.50R17LT	10PR 125R	CVPTHRT02R	10J	8.0-10.5	34.52	12.50	15.7	RWL	N
18"	LT265/65R18	10PR 122/119Q	CVPTHRT40	8 J	8.0-9.5	31.54	10.31	15.7	BLK	Y
	LT265/65R18	10PR 122/119Q	CVPTHRT40R	8 J	8.0-9.5	31.54	10.31	15.7	RWL	Y
	LT275/70R18	10PR125/122R	CVPTHRT25	8 J	7.0-9.0	33.19	10.98	15.7	BLK	N
	LT275/70R18	10PR125/122R	CVPTHRT25R	8 J	7.0-9.0	33.19	10.98	15.7	RWL	N
	LT285/60R18	10PR 122/119Q	CVPTHRT33	8 1/2J	8.5-10.0	31.46	11.50	15.7	BLK	N
	LT285/60R18	10PR 122/119Q	CVPTHRT33R	8 1/2J	8.5-10.0	31.46	11.50	15.7	RWL	N
	LT285/65R18	10PR 125/122R	CVPTHRT26	8 1/2J	8.5-10.0	32.56	11.50	15.7	BLK	N
	LT285/65R18	10PR 125/122R	CVPTHRT26R	8 1/2J	8.5-10.0	32.56	11.50	15.7	RWL	N

✦ Every effort has been made to verify the accuracy of the listed specifications. Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.





WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
18"	LT295/70R18	10PR 129/126Q	CVPTHRT37	8 1/2J	7.5-10.0	34.29	11.77	15.7	BLK	N
	LT295/70R18	10PR 129/126Q	CVPTHRT37R	8 1/2J	7.5-10.0	34.29	11.77	15.7	RWL	N
	33X12.50R18LT	10PR 118Q	CVPTHRT03	10J	8.5-11.0	32.52	12.50	15.7	BLK	N
	33X12.50R18LT	10PR 118Q	CVPTHRT03R	10J	8.5-11.0	32.52	12.50	15.7	RWL	N
	35X12.50R18LT	10PR 123R	CVPTHRT04	10J	8.5-11.0	34.52	12.50	15.7	BLK	N
	35X12.50R18LT	10PR 123R	CVPTHRT04R	10J	8.5-11.0	34.52	12.50	15.7	RWL	N
20"	275/60R20	115T	CVPTHRT30	8 J	7.5-9.5	32.99	10.98	12.2	BLK	N
	275/60R20	115T	CVPTHRT30R	8 J	7.5-9.5	32.99	10.98	12.2	RWL	N
	LT275/55R20	10PR 120/117S	CVPTHRT05	8 1/2J	8.0-9.5	31.89	11.18	15.7	BLK	N
	LT275/60R20	10PR 123/120R	CVPTHRT24	8 J	8.0-9.5	32.99	10.98	15.7	BLK	N
	LT275/60R20	10PR 123/120R	CVPTHRT24R	8 J	8.0-9.5	32.99	10.98	15.7	RWL	N
	LT285/55R20	10PR 122/119Q	CVPTHRT06	9J	8.5-10.0	32.36	11.69	15.7	BLK	N
	LT285/55R20	10PR 122/119Q	CVPTHRT06R	9J	8.5-10.0	32.36	11.69	15.7	RWL	N
	LT285/60R20	10PR 125/122R	CVPTHRT07	8 1/2J	8.5-10.0	33.46	11.50	15.7	BLK	N
	LT285/60R20	10PR 125/122R	CVPTHRT07R	8 1/2J	8.5-10.0	33.46	11.50	15.7	RWL	N
	33X11.50R20LT	10PR 118Q	CVPTHRT08	9J	8.0-10.5	32.52	11.42	15.7	BLK	N
	33X11.50R20LT	10PR 118Q	CVPTHRT08R	9J	8.0-10.5	32.52	11.42	15.7	RWL	N
	33X12.50R20LT	10PR 114Q	CVPTHRT01	10J	8.5-11.0	32.52	12.50	17.0	BLK	N
	33X12.50R20LT	10PR 114Q	CVPTHRT01R	10J	8.5-11.0	32.52	12.50	17.0	RWL	N
	33X12.50R20LT	12PR 119Q	CVPTHRT10	10J	8.5-11.0	32.52	12.50	17.0	BLK	N
	33X12.50R20LT	12PR 119Q	CVPTHRT10R	10J	8.5-11.0	32.52	12.50	17.0	RWL	N
	35X12.50R20LT	10PR 121Q	CVPTHRT11	10J	8.5-11.0	34.52	12.50	15.7	BLK	N
	35X12.50R20LT	10PR 121Q	CVPTHRT11R	10J	8.5-11.0	34.52	12.50	15.7	RWL	N
	35X12.50R20LT	12PR 125Q	CVPTHRT12	10J	8.5-11.0	34.52	12.50	15.7	BLK	N
	35X12.50R20LT	12PR 125Q	CVPTHRT12R	10J	8.5-11.0	34.52	12.50	15.7	RWL	N
	37X11.50R20LT	10PR 128Q	CVPTHRT42	9J	7.5-10.0	36.52	11.42	15.7	BLK	N
	37X12.50R20LT	12PR 128Q	CVPTHRT20	10J	8.5-11.0	36.52	12.50	15.7	BLK	N
	37X12.50R20LT	12PR 128Q	CVPTHRT20R	10J	8.5-11.0	36.52	12.50	15.7	RWL	N
	37X13.50R20LT	10PR 127Q	CVPTHRT31R	11J	9.5-12.0	36.52	13.58	15.7	RWL	N
	37X13.50R20LT	10PR 127Q	CVPTHRT43	11J	9.5-12.0	36.52	13.58	15.7	BLK	N

✦ Every effort has been made to verify the accuracy of the listed specifications. Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.



WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
20"	37X13.50R20LT	12PR 128Q	CVPTHRT13	11J	9.5-12.0	36.52	13.58	15.7	BLK	N
	37X13.50R20LT	12PR 128Q	CVPTHRT13R	11J	9.5-12.0	36.52	13.58	15.7	RWL	N
22"	33X12.50R22LT	10PR 109R	CVPTHRT14	10J	10.0-12.0	32.52	12.45	17.0	BLK	N
	33X12.50R22LT	12PR 114Q	CVPTHRT15	10J	10.0-12.0	32.52	12.45	17.0	BLK	N
	35X12.50R22LT	10PR 117R	CVPTHRT16	10J	8.5-11.0	34.52	12.50	15.7	BLK	N
	35X12.50R22LT	10PR 117R	CVPTHRT16R	10J	8.5-11.0	34.52	12.50	15.7	RWL	N
	35X12.50R22LT	12PR 121Q	CVPTHRT17	10J	8.5-11.0	34.52	12.50	15.7	BLK	N
	35X12.50R22LT	12PR 121Q	CVPTHRT17R	10J	8.5-11.0	34.52	12.50	15.7	RWL	N
	37X12.50R22LT	12PR 127Q	CVPTHRT19	10J	8.5-11.0	36.52	12.50	15.7	BLK	N
	37X12.50R22LT	12PR 127Q	CVPTHRT19R	10J	8.5-11.0	36.52	12.50	15.7	RWL	N
	37X13.50R22LT	10PR 123Q	CVPTHRT21R	11J	9.5-12.0	36.52	13.58	15.7	RWL	N
	37X13.50R22LT	10PR 123Q	CVPTHRT44	11J	9.5-12.0	36.52	13.58	15.7	BLK	N
26"	37X13.50R22LT	12PR 128Q	CVPTHRT18	11J	9.5-12.0	36.52	13.58	15.7	BLK	N
	37X13.50R22LT	12PR 128Q	CVPTHRT18R	11J	9.5-12.0	36.52	13.58	15.7	RWL	N
26"	LT305/35R26	10PR 108/104Q	CVPTHRT41	11J	10.0-12.0	34.41	12.32	15.7	BLK	N

✦ Every effort has been made to verify the accuracy of the listed specifications. Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.

TRAIL HUNTER ATX

ON- AND OFF-ROAD MAX TRACTION ALL-TERRAIN TIRE

The Trail Hunter ATX packs serious traction without the noise, offering a perfect balance of performance and comfort for your daily commuter truck or SUV. Built for versatility, it's ready to tackle any terrain with confidence.



- Advanced all-terrain tread compound for extended treadlife and superior on- and off-road grip.
- Tread pattern and pitch variation minimize road noise, ensuring a smoother highway ride and increased comfort for all occupants.
- Deep, multi-functional tread grooves and siping deliver enhanced traction across diverse road conditions.
- Stepped shoulder lugs provide extra biting edges for improved traction on rocky terrain.
- Extensive block siping along the tire circumference enhances handling stability, grip, and braking in winter and wet conditions.
- Mud and stone ejectors between tread blocks prevent buildup and stone drilling.
- Dual sidewall design offers two stylish looks while delivering added off-road traction and sidewall armor.
- Available in 20-inch and 22-inch light truck sizes.

ROAD HAZARD

4 YEARS WARRANTY

3PLY SELECTED SIZES

FULL TREAD DEPTH

WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
20"	LT285/55R20	10PR122/119Q	VP THATX01	9J	8.5-10.0	32.36	11.69	15.1	BLK	N
	33X12.50R20LT	10PR114Q	VP THATX02	10J	8.5-11.0	32.52	12.50	14.7	BLK	N
	33X12.50R20LT	12PR119Q	VP THATX03	10J	8.5-11.0	32.52	12.50	14.7	BLK	N
	35X12.50R20LT	10PR 121Q	VP THATX04R	10J	8.5-11.0	34.52	12.50	15.1	RWL	N
	35X12.50R20LT	12PR 125Q	VP THATX05R	10J	8.5-11.0	34.52	12.50	15.1	RWL	N
22"	33X12.50R22LT	10PR109R	VP THATX06	10J	10.0-12.0	32.52	12.45	14.5	BLK	N



† Every effort has been made to verify the accuracy of the listed specifications. Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.



TRAIL HUNTER ATS

ALL-TERRAIN PERFORMANCE TIRE FOR CROSSOVERS AND LIGHT TRUCKS

Introducing the Trail Hunter ATS, a hybrid tire crafted for light trucks, SUVs, and crossover vehicles. Offering superior all-terrain traction without compromising street performance, it instills confidence in various weather conditions and off-road adventures while ensuring a smooth and quiet ride on pavement.



- Evenly spaced tread blocks and intermediate void-to-lug ratio for balanced on- and off-road performance for light trucks, SUVs, and crossovers.
- ATS siping in tread block grooves enhances wet and winter driving traction.
- Dual-stage shoulder lugs improve biting edges on rocky terrain.
- Computer-aided variable block pitch, spacing, and arrangement minimize road noise, ensuring a smoother and more comfortable ride for both drivers and passengers.
- A binary sidewall design with 3-dimensional wedge-shaped lugs on one side and swooping convex fang-shaped lugs on the opposite side, offers enthusiasts aesthetic options for their vehicles.
- Available in 20-inch and 22-inch light truck (LT) sizes, and 17-inch to 24-inch P-Metric sizes.

WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
17"	215/65R17	103T XL	VPTHATS29	6 1/2J	6.0-7.5	28.03	8.70	11.0	BLK	N
	225/55R17	101H XL	VPTHATS30	7J	6.0-8.0	26.77	9.17	11.0	BLK	N
	225/60R17	103H XL	VPTHATS31	6 1/2J	6.0-8.0	27.64	9.0	11.0	BLK	N
	225/65R17	106H XL	VPTHATS32	6 1/2J	6.0-8.0	28.50	8.98	11.0	BLK	N
	235/55R17	103H XL	VPTHATS33	7 1/2J	6.5-8.5	27.17	9.65	11.0	BLK	N
	235/65R17	108H XL	VPTHATS34	7J	6.5-8.5	29.06	9.45	11.0	BLK	N
	245/65R17	107H	VPTHATS06	7J	7.0-8.5	29.53	9.76	10.6	BLK	N
	265/70R17	115S	VPTHATS35	8J	7.0-9.0	31.65	10.71	11.0	BLK	N
	LT265/70R17	10PR 123/120S	VPTHATS24	8J	7.0-9.0	31.65	10.71	14.5	BLK	N
	LT285/70R17	10PR 126/123S	VPTHATS25	8 1/2J	7.5-9.5	32.76	11.50	14.5	BLK	N
18"	225/55R18	102H XL	VPTHATS36	7J	6.0-8.0	27.76	9.17	11.0	BLK	N
	225/60R18	104H XL	VPTHATS37	6 1/2J	6.0-8.0	28.62	9.0	11.0	BLK	N
	235/55R18	104H XL	VPTHATS39	7 1/2J	6.5-8.5	28.15	9.7	11.0	BLK	N
	235/60R18	107V XL	VPTHATS38	7J	6.5-8.5	29.09	9.5	11.0	BLK	N
	235/65R18	110H XL	VPTHATS40	7J	6.5-8.5	30.04	9.45	11.0	BLK	N
	245/60R18	109H XL	VPTHATS45	7J	7.0-8.5	29.57	9.8	11.0	BLK	N
	255/55R18	113V XL	VPTHATS08A	8J	7.0-9.0	29.02	10.43	11.0	BLK	N
	255/65R18	111H	VPTHATS09	7 1/2J	7.0-9.0	31.06	10.24	11.0	BLK	N
	255/65R18	115T XL	VPTHATS46	7 1/2J	7.0-9.0	31.06	10.24	11.0	BLK	N
	LT275/70R18	10PR 125/122S	VPTHATS26	8J	7.0-9.0	33.19	10.98	14.5	BLK	N
19"	235/55R19	105V XL	VPTHATS10	7 1/2J	6.5-8.5	29.17	9.65	11.0	BLK	N
	245/45R19	102V XL	VPTHATS41	8J	7.5-9.0	27.68	9.57	11.0	BLK	N
	245/55R19	103V	VPTHATS11	7 1/2J	7.0-8.5	29.65	9.96	11.0	BLK	N
	255/55R19	111V XL	VPTHATS12	8J	7.0-9.0	30.04	10.43	11.0	BLK	N
20"	245/45R20	103H XL	VPTHATS42	8J	7.5-9.0	28.66	9.57	11.0	BLK	N
	245/50R20	106H XL	VPTHATS13	7 1/2J	7.0-8.5	29.69	9.96	11.0	BLK	N
	255/50R20	109T XL	VPTHATS14	8J	7.0-9.0	30.08	10.43	11.0	BLK	N
	255/55R20	110H XL	VPTHATS15	8J	7.0-9.0	31.02	10.43	11.0	BLK	N
	265/50R20	111H XL	VPTHATS16	8 1/2J	7.5-9.5	30.47	10.91	11.0	BLK	N
	275/45R20	110H XL	VPTHATS17	9J	8.5-10.5	29.76	10.75	11.0	BLK	N
	275/55R20	117T XL	VPTHATS18	8 1/2J	7.5-9.5	31.89	11.18	11.0	BLK	N
	275/60R20	116H XL	VPTHATS43	8J	7.5-9.5	32.99	10.98	11.0	BLK	N
	285/50R20	116H XL	VPTHATS44	9J	8.0-10	31.26	11.69	11.0	BLK	N
	LT285/55R20	10PR 122/119Q	VPTHATS01	9J	8.5-10.0	32.36	11.69	13.9	BLK	N
	33X12.50R20LT	10PR 114R	VPTHATS02	10J	8.5-11.0	32.52	12.50	14.5	BLK	N
	33X12.50R20LT	12PR 119R	VPTHATS03	10J	8.5-11.0	32.52	12.50	14.5	BLK	N
	35X12.50R20LT	10PR 121Q	VPTHATS27	10J	8.5-11.0	34.52	12.5	17.6	BLK	N
	35X12.50R20LT	12PR 125Q	VPTHATS28	10J	8.5-11.0	34.5	12.5	18	BLK	N
22"	265/35R22	102V XL	LVPTHATS22	9 1/2J	9.0-10.5	29.33	10.67	11.0	BLK	N
	275/45R22	112H XL	VPTHATS19	9J	8.5-10.5	31.77	10.75	11.0	BLK	N
	285/45R22	114H XL	VPTHATS20	9 1/2J	9.0-10.5	32.09	11.22	11.0	BLK	N
	305/40R22	114V XL	LVPTHATS23	11J	10.0-12.0	31.61	12.32	11.0	BLK	N
24"	305/35R24	112H XL	VPTHATS21	11J	10.0-12.0	32.44	12.32	11.0	BLK	N

+ Every effort has been made to verify the accuracy of the listed specifications. Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.

LIGHT TRUCK WINTER TIRE

UNLEASH THE APEX PREDATOR WITHIN YOUR DRIVE WITH THE ICE HUNTER WTS LIGHT TRUCK TIRE. INSPIRED BY THE SHARK, NATURE'S ULTIMATE PREDATOR, THIS TIRE CONQUERS WINTER DRIVING CONDITIONS WITH UNPARALLELED POWER AND CONTROL. FEATURING A STUDDABLE, ASYMMETRICAL TREAD BLOCK DESIGN, IT DELIVERS EXCEPTIONAL ON-HIGHWAY PERFORMANCE WITHOUT SACRIFICING OFF-ROAD CAPABILITIES. THE TIRE'S AGGRESSIVE PROFILE, COMPLETE WITH SHARK-INSPIRED FIN MARKINGS AND SHARK TEETH CIRCLING THE BEAD, REINFORCES ITS DOMINANCE. ENGINEERED FOR SUPREMACY IN WINTER CONDITIONS, THE ICE HUNTER WTS PROVIDES EXCEPTIONAL TRACTION, HANDLING, AND DURABILITY, MAKING IT THE TOP PREDATOR OF WINTER TIRES.

ICE HUNTER WT



ICE HUNTER WTS

LIGHT TRUCK WINTER TIRE

- Facebook
venompowertires
- Instagram
venompowertires
- TikTok
venompowertires
- YouTube
venompowertires



- The Ice Hunter WTS is M+S and 3PMSF certified for reliable performance in severe winter conditions.
- Advanced winter tread compound enhances traction and balance in winter driving conditions.
- Asymmetrical tread block geometry ensures high levels of highway performance without compromising off-road capabilities.
- Wide circumferential and lateral grooves are designed to efficiently evacuate water and slush, minimizing aquaplaning and slushplaning.
- Increased sipe density and ripple design enhance the biting edge for additional handling stability.
- Large shoulder blocks improve responsiveness during cornering.



WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
16"	235/65R16C	10PR 118/116R	VPWTS23	7J	6.5-7.5	28.03	9.45	14.20	BLK	Y
	LT265/70R17	10PR 123/120R	VPWTS24	8J	7.0-9.0	31.65	10.71	14.20	BLK	Y
17"	LT285/70R17	10PR 126/123R	VPWTS25	8 1/2J	7.5-9.5	32.76	11.50	14.20	BLK	Y
	33X12.50R17LT	10PR 120Q	VPWTS26	10J	8.5-11.0	32.52	12.50	15.50	BLK	Y
	35X12.50R17LT	10PR 125R	VPWTS27	10J	8.0-10.5	34.52	12.50	15.50	BLK	Y
	LT275/65R18	10PR 123/120R	VPWTS29	8J	8.0-9.5	32.09	10.98	14.20	BLK	Y
18"	LT275/70R18	10PR 125/122R	VPWTS28	8J	7.0-9.0	33.19	10.98	14.20	BLK	Y
	33X12.50R18LT	10PR 118Q	VPWTS30	10J	8.5-11.0	32.52	12.50	15.50	BLK	Y
	35X12.50R18LT	10PR 123R	VPWTS31	10J	8.5-11.0	34.52	12.50	15.50	BLK	Y
	235/50R19	103H XL	VPWTS38	7 1/2J	6.5-8.5	28.31	9.65	12.00	BLK	Y
19"	235/55R19	105H XL	VPWTS39	7 1/2J	6.5-8.5	29.17	9.65	12.00	BLK	Y
	255/60R19	113T XL	VPWTS43	7 1/2J	7.0-9.0	31.06	10.24	12.00	BLK	Y
	245/50R20	102T	VPWTS18	7 1/2J	7.0-8.5	29.69	9.96	12.00	BLK	Y
20"	255/50R20	109H XL	VPWTS40	8J	7.0-9.0	30.08	10.43	12.00	BLK	Y
	255/55R20	110H XL	VPWTS41	8J	7.0-9.0	31.02	10.43	12.00	BLK	Y
	265/50R20	107T	VPWTS19	8 1/2J	7.5-9.5	30.47	10.91	12.00	BLK	Y
	275/55R20	117TXL	VPWTS20	8 1/2J	7.5-9.5	31.89	11.18	12.00	BLK	Y
	275/60R20	115T	VPWTS21	8J	7.5-9.5	32.99	10.98	12.00	BLK	Y
	LT275/65R20	10PR 126/123R	VPWTS37	8J	8.0-9.5	34.09	10.98	14.20	BLK	Y
	LT285/60R20	10PR 125/122R	VPWTS44	8 1/2J	8.5-10.0	33.46	11.50	14.20	BLK	Y
	33X12.50R20LT	10PR 114Q	VPWTS32	10J	8.5-11.0	32.52	12.50	16.70	BLK	Y
	35X12.50R20LT	10PR 121Q	VPWTS33	10J	8.5-11.0	34.52	12.50	15.50	BLK	Y
	37X13.50R20LT	10PR 127Q	VPWTS36	11J	9.5-12.0	36.52	13.58	16.70	BLK	Y
	275/40R22	107HXL	VPWTS42	9 1/2J	9.0-11.0	30.67	10.94	12.00	BLK	Y
	275/50R22	115T XL	VPWTS45	8 1/2J	7.5-9.5	32.87	11.18	12.00	BLK	Y
22"	285/45R22	114TXL	VPWTS22	9 1/2J	9.0-10.5	32.09	11.22	12.00	BLK	Y
	33X12.50R22LT	10PR 109R	VPWTS34	10 1/2J	10.0-12.0	32.52	12.45	16.70	BLK	Y
	35X12.50R22LT	10PR 117R	VPWTS35	10J	8.5-11.0	34.52	12.50	15.50	BLK	Y

† Every effort has been made to verify the accuracy of the listed specifications. Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.



ALL-SEASON HIGH PERFORMANCE TIRE

WIELD THE POWER AND PERFORMANCE OF VENOM POWER'S RAGNAROK GTS. THIS HIGH-PERFORMANCE, ALL-SEASON TIRE FEATURES A STRIKING SIDEWALL DESIGN AND NEXT-GEN TREAD PATTERN WHICH ELEVATES YOUR VEHICLE'S AESTHETICS WHILE DELIVERING EXCEPTIONAL PERFORMANCE YEAR-ROUND. ENGINEERED FOR THOSE WHO DEMAND EXCELLENCE, THE RAGNAROK GTS ENABLES YOU TO CONQUER CHALLENGING ROAD CONDITIONS WITH UNPARALLELED GRIP, CONTROL, AND DURABILITY, TRANSFORMING EVERY DRIVE INTO A THRILLING SAGA OF POWER AND PRECISION.

RAGNAROK GT



RAGNAROK GT S

ALL-SEASON HIGH PERFORMANCE TIRE

- Facebook
venompowertires
- Instagram
venompowertires
- TikTok
venompowertires
- YouTube
venompowertires



WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
16"	225/50ZR16	96W	TVPGTS89	7J	6.0-8.0	24.88	9.17	10.1	BLK	N
	245/50ZR16	97W	TVPGTS88	7.5J	7.0-8.5	25.67	9.96	10.1	BLK	N
	255/50ZR16	99W	TVPGTS90	8J	7.0-9.0	26.06	10.43	10.1	BLK	N
17"	215/55ZR17	98WXL	TVPGTS42	7J	6.0-7.5	26.30	8.90	10.3	BLK	N
	315/35ZR17	102W	TVPGTS78	11J	10.5-12.5	25.67	12.60	10.1	BLK	N
18"	245/45ZR18	100W XL	TVPGTS43	8J	7.5-9.0	26.65	9.57	10.3	BLK	N
	255/50R18	106V XL	TVPGTS76	8J	7.0-9.0	28.07	10.43	9.1	BLK	N
19"	225/35ZR19	88W XL	TVPGTS85	8J	7.5- 9.0	26.22	9.06	10.1	BLK	N
20"	225/30ZR20	85W XL	CVPGTS22	8J	8.0	25.35	9.06	10.3	BLK	N



- Asymmetrical tread block geometry for even wear, durability, and high-level highway performance.
- Large directional shoulder blocks for enhanced braking and cornering responsiveness.
- Edge block siping along both shoulders for additional handling stability.
- Wide circumferential and lateral grooves that efficiently channel water away to minimize hydroplaning, providing confidence on wet roads.
- Available in a wide range of sizes (17" to 28") to fit sport coupes, luxury sedans, crossovers, light trucks, and SUVs.



WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
20"	235/30ZR20	88W XL	CVPGTS23	8 1/2J	8.5	25.59	9.49	10.1	BLK	N
	235/35ZR20	92W XL	CVPGTS24	8 1/2J	8.0-9.5	26.46	9.49	10.3	BLK	N
	245/30ZR20	90W XL	CVPGTS25	8 1/2J	8.0-9.0	25.83	9.76	10.3	BLK	N
	245/35ZR20	95W XL	CVPGTS02	8 1/2J	8.0-9.5	26.77	9.76	10.3	BLK	N
	245/40ZR20	99W XL	TVPGTS44	8 1/2J	8.0-9.5	27.72	9.76	10.3	BLK	N
	245/45ZR20	103W XL	TVPGTS45	8J	7.5-9.0	28.66	9.57	10.3	BLK	N
	255/30ZR20	92W XL	CVPGTS26	9J	8.5-9.5	26.06	10.24	10.1	BLK	N
	265/45R20	108V XL	SVPGTS02	9J	8.5-10.0	29.37	10.47	10.1	BLK	N
	275/30ZR20	97W XL	TVPGTS46	9 1/2J	9.0-10.0	26.54	10.94	10.3	BLK	N
	275/35ZR20	102W XL	TVPGTS47	9 1/2J	9.0-11.0	27.56	10.94	10.3	BLK	N
	275/40ZR20	106W XL	TVPGTS48	9 1/2J	9.0-11.0	28.66	10.94	10.3	BLK	N
	275/45ZR20	110W XL	TVPGTS83	9J	8.5-10.5	29.76	10.75	10.1	BLK	N
	275/55R20	117H XL	TVPGTS49	8 1/2J	7.5-9.5	31.89	11.18	10.3	BLK	N
	275/60R20	116H XL	TVPGTS50	8J	7.5-9.5	32.99	10.98	10.3	BLK	N
	285/25ZR20	93W XL	CVPGTS27	10 1/2J	10.5	25.59	11.61	10.1	BLK	N
	285/30ZR20	99W XL	TVPGTS51	10J	9.5-10.5	26.77	11.42	10.3	BLK	N
	285/35ZR20	104Y XL	TVPGTS52	10J	9.5-11.0	27.87	11.42	10.3	BLK	N
	285/40R20	108V XL	SVPGTS05	10J	9.5-11.0	28.98	11.42	10.1	BLK	N
	285/50R20	116V XL	SVPGTS06	9J	8.0-10.0	31.26	11.69	10.1	BLK	N
	295/25ZR20	95W XL	CVPGTS28	10 1/2J	10.0-11.0	25.83	11.85	10.1	BLK	N
	295/30ZR20	101Y XL	CVPGTS29	10 1/2J	10.0-11.0	27.01	11.85	10.1	BLK	N
	295/40ZR20	110 XL W	SVPGTS15	10 1/2J	10.0-11.5	29.29	11.85	10.1	BLK	N
	295/45R20	114V XL	SVPGTS08	10J	9.5-11.0	30.47	11.65	10.1	BLK	N
	305/35R20	107W XL	TVPGTS82	11 J	10.0-12.0	28.43	12.32	10.1	BLK	N
	305/50R20	120H XL	CVPGTS30	9 1/2J	8.5-11.0	32.05	12.44	10.1	BLK	N
	315/35ZR20	110W XL	TVPGTS53	11 J	10.5-12.5	28.66	12.60	10.3	BLK	N
	LT305/50R20	12PR 122J/119S	SVPGTS11	9 1/2J	9.0-11.0	32.05	12.44	13.9	BLK	N
	LT325/50R20	12PR 124S	SVPGTS14	10J	9.5-11.5	32.83	13.23	13.9	BLK	N
	33X12.50R20LT	12PR 119R	TVPGTS01	10J	8.5-11.0	32.52	12.50	13.9	BLK	N
22"	225/30ZR22	87W XL	CVPGTS04	8J	8.0	27.36	9.06	10.3	BLK	N

WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
22"	235/30ZR22	90W XL	CVPGTS05	8 1/2J	8.5	27.60	9.49	10.3	BLK	N
	245/30ZR22	92W XL	CVPGTS06	8 1/2J	8.0-9.0	27.83	9.76	10.3	BLK	N
	255/30ZR22	95W XL	CVPGTS07	9J	8.5-9.5	28.07	10.24	10.3	BLK	N
	265/30ZR22	97W XL	CVPGTS08	9 1/2J	9.0-10.0	28.31	10.67	10.3	BLK	N
	265/35R22	102V XL	TVPGTS54	9 1/2J	9.0-10.5	29.33	10.67	10.3	BLK	N
	265/40R22	106V XL	SVPGTS01	9 1/2J	9-10.5	30.35	10.67	10.1	BLK	N
	275/25ZR22	93Y XL	CVPGTS31	10J	10.0	27.44	11.14	10.1	BLK	N
	275/35ZR22	104Y XL	TVPGTS84	9 1/2J	9.0-11.0	29.57	10.94	10.1	BLK	N
	275/40ZR22	107Y XL	CVPGTS11	9 1/2J	9.0-11.0	30.67	10.94	10.3	BLK	N
	275/45R22	112V XL	SVPGTS03	9J	8.5-10.5	31.77	10.75	10.1	BLK	N
	275/50R22	111H	SVPGTS04	8 1/2J	7.5-9.5	32.87	11.18	10.1	BLK	N
	285/25ZR22	95W XL	CVPGTS32	10 1/2J	10.5	27.60	11.61	10.1	BLK	N
	285/35R22	106V XL	CVPGTS10	10J	9.5-11.0	29.88	11.42	10.3	BLK	N
	285/40ZR22	110W XL	CVPGTS12	10J	9.5-11.0	30.98	11.42	10.3	BLK	N
	285/45R22	114V XL	TVPGTS55	9 1/2J	9.0-10.5	32.09	11.22	10.3	BLK	N
	295/25ZR22	97W XL	CVPGTS03	10 1/2J	10.0-11.0	27.83	11.85	10.3	BLK	N
	295/30ZR22	103W XL	CVPGTS09	10 1/2J	10.0-11.0	29.02	11.85	10.3	BLK	N
	295/30R22	103V XL	SVPGTS07	10 1/2J	10.0-11.0	29.02	11.85	10.1	BLK	N
	305/30ZR22	105Y XL	CVPGTS33	11J	10.5-11.5	29.25	12.32	10.1	BLK	N
	305/35ZR22	110W XL	CVPGTS34	11J	10.0-12.0	30.43	12.32	10.1	BLK	N
	305/40R22	114V XL	TVPGTS56	11J	10.0-12.0	31.61	12.32	10.3	BLK	N
	305/45R22	118V XL	TVPGTS57	10J	9.5-11.5	32.80	11.93	10.3	BLK	N
	315/25ZR22	101Y XL	CVPGTS35	11 1/2J	11.0-12.0	28.23	12.80	10.1	BLK	N
	315/30ZR22	107Y XL	CVPGTS36	11J	10.5-11.5	29.49	12.60	10.1	BLK	N
	325/35ZR22	114W XL	SVPGTS10	11 1/2J	11.0-13.0	30.98	13.03	10.1	BLK	N
	LT305/50R22	12PR 124/121S	SVPGTS12	9 1/2J	9.0-11.0	34.06	12.44	13.9	BLK	N
	LT315/45R22	12PR 121/118S	SVPGTS13	10 1/2J	10.0-12.0	33.19	12.40	13.9	BLK	N
23"	305/40R23	115H XL	SVPGTS09	11 J	10.0-12.0	32.6	12.32	10.1	BLK	N
24"	245/30ZR24	94W XL	CVPGTS13	8 1/2J	8.0-9.0	29.84	9.76	10.3	BLK	N
	255/25ZR24	91W XL	TVPGTS79	9J	9J	28.82	10.79	10.1	BLK	N





WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
24"	255/30ZR24	97W XL	TVPGTS58	9J	8.5-9.5	30.08	10.24	10.3	BLK	N
	265/25ZR24	93W XL	TVPGTS91	9 1/2J	9.0-10.0	29.21	10.67	10.1	BLK	N
	275/23ZR24	93W XL	TVPGTS80	10J	9.5-10.5	28.90	11.73	10.1	BLK	N
	275/25ZR24	96W XL	TVPGTS59	10J	9.5-10.5	29.45	11.14	10.3	BLK	N
	275/30ZR24	101W XL	CVPGTS14	9 1/2J	9.0-10.0	30.55	10.94	10.3	BLK	N
	275/35ZR24	106W XL	CVPGTS37	9 1/2J	9.0-11.0	31.57	10.94	10.1	BLK	N
	285/35R24	108V XL	CVPGTS38	10J	9.5-11.0	31.89	11.42	10.1	BLK	N
	285/40R24	112V XL	CVPGTS17	10J	9.5-11.0	32.99	11.42	10.3	BLK	N
	295/30R24	105V XL	CVPGTS15	10 1/2J	10.0-11.0	31.02	11.85	10.3	BLK	N
	295/35R24	110V XL	CVPGTS16	10 1/2J	10.0-11.5	32.13	11.85	10.3	BLK	N
	305/35R24	112V XL	TVPGTS60	11J	10.0-12.0	32.44	12.32	10.3	BLK	N
	335/30ZR24	112W XL	TVPGTS93	12J	11.5-12.5	31.97	13.5	10.1	BLK	N
	405/25ZR24	116W XL	CVPGTS42	14 1/2J	14.0-15.0	31.97	16.34	11.1	BLK	N
	33X13.50R24LT	12PR 113S	CVPGTS21	12 J	11.5-12.5	32.52	13.58	13.9	BLK	N
	33X14.50R24LT	12PR 118Q	TVPGTS87	13J	12.5-14.0	33.00	14.5	13.9	BLK	N
26"	255/30ZR26	99W XL	CVPGTS39	9J	8.5-9.5	32.09	10.24	10.1	BLK	N
	275/25ZR26	98W XL	TVPGTS92	10J	9.5-10.5	31.42	11.14	10.1	BLK	N
	295/25ZR26	102W XL	CVPGTS40	10 1/2J	10.0-11.0	31.81	11.85	10.1	BLK	N
	295/30ZR26	107W XL	CVPGTS18	10 1/2J	10.0-11.0	32.99	11.85	10.3	BLK	N
	305/30ZR26	109W XL	CVPGTS19	11J	10.5-11.5	33.23	12.32	10.3	BLK	N
28"	255/30ZR28	101W XL	TVPGTS77	9J	8.5-9.5	34.09	10.24	10.1	BLK	N
	275/25ZR28	101W XL	CVPGTS41	10J	10.0	33.46	11.14	10.1	BLK	N
	295/25ZR28	103W XL	CVPGTS20	10 1/2J	10.0-11.0	33.82	11.85	10.3	BLK	N

✦ Every effort has been made to verify the accuracy of the listed specifications. Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.




ALL-SEASON ULTRA-HIGH-PERFORMANCE (UHP)

THE VENOM POWER COVERT GRIP ASP IS AN ALL-SEASON ULTRA-HIGH-PERFORMANCE (UHP) TIRE ENGINEERED TO PROVIDE EXCEPTIONAL HANDLING AND GRIP IN ALL WEATHER CONDITIONS FOR A VARIETY OF VEHICLES, INCLUDING PASSENGER CARS, CROSOVERS, AND SUVS. THIS IS ACHIEVED THROUGH ITS UNIQUE ASYMMETRICAL TREAD DESIGN, WHERE THE INNER AND OUTER TREAD PATTERNS DIFFER TO OPTIMIZE PERFORMANCE BASED ON THE SPECIFIC CONTACT PATCH AREA.

COVERT GRIP ASP

COVERT GRIP ASP

ALL-SEASON ULTRA-HIGH-PERFORMANCE (UHP)



WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	EV READY
14"	175/65R14	82H	VPCGASP129	5J	5.0-6.0	22.99	6.97	8.9	BLK	-
	185/60R14	82H	VPCGASP139	5 1/2J	5.0-6.5	22.76	7.44	9.7	BLK	-
	185/65R14	86H	VPCGASP140	5 1/2J	5.0-6.5	23.46	7.44	9.7	BLK	-
	185/70R14	88H	VPCGASP130	5 1/2J	4.5-6.0	24.25	7.44	10.0	BLK	-
15"	175/65R15	84H	VPCGASP141	5J	5.0-6.0	23.98	6.97	8.9	BLK	-
	185/55R15	82H	VPCGASP131	6J	5.0-6.5	23.03	7.64	10.0	BLK	-
	185/60R15	84H	VPCGASP122	5 1/2J	5.0-6.5	23.74	7.44	9.7	BLK	-
	185/65R15	88H	VPCGASP142	5 1/2J	5.0-6.5	24.45	7.44	9.7	BLK	-
	195/50R15	82V	VPCGASP132	6J	5.5-7.0	22.72	7.91	10.0	BLK	-
	195/55R15	85V	VPCGASP143	6J	5.5-7.0	23.43	7.91	10.0	BLK	-
	195/60R15	88 V	VPCGASP109	6J	5.5-7.0	24.21	7.91	9.7	BLK	-
	195/65R15	91H	VPCGASP123	6J	5.5-7.0	25	7.91	10.0	BLK	-
	205/50R15	89V XL	VPCGASP133	6 1/2J	5.5-7.5	23.11	8.43	10.0	BLK	-
	205/60R15	91H	VPCGASP144	6J	5.5-7.5	24.69	8.23	10.0	BLK	-
	205/65R15	94 H	VPCGASP125	6J	5.5-7.5	25.47	8.23	10.0	BLK	-
	205/70R15	100H XL	VPCGASP111	6J	5.0-7.0	26.34	8.23	10.0	BLK	-
	215/70R15	98 H	VPCGASP128	6 1/2J	5.5-7.0	26.89	8.70	10.0	BLK	-
	185/55R16	83V	VPCGASP134	6J	5.0-6.5	24.02	7.64	10.0	BLK	-
16"	195/50R16	84V	VPCGASP135	6J	5.5-7.0	23.70	7.91	10.0	BLK	-
	195/55R16	87 V	VPCGASP108	6J	5.5-7.0	24.41	7.91	10.0	BLK	-
	205/50ZR16	87 W	VPCGASP110	6 1/2J	5.5-7.5	24.09	8.43	9.7	BLK	-
	205/55R16	91W	VPCGASP02	6 1/2J	5.5-7.5	24.88	8.43	10.0	BLK	-
	205/60R16	92 V	VPCGASP124	6J	5.5-7.5	25.67	8.23	9.7	BLK	-
	205/65R16	95 H	VPCGASP126	6J	5.5-7.5	26.46	8.23	9.7	BLK	-
	205/70R16	97H	VPCGASP136	6J	5.0-7.0	27.32	8.23	10.0	BLK	-
	215/55R16	97V XL	VPCGASP112	7J	6.0-7.5	25.28	8.90	9.7	BLK	-
	215/60R16	95V	VPCGASP145	6 1/2J	6.0-7.5	26.14	8.7	10.0	BLK	-

- Innovative tread compound delivers high grip and braking performance in both wet and dry conditions.
- Unique tread block design enhances comfort and reduces harmonic road noise for a quieter ride.
- Dual circumferential grooves effectively channels water and slush away from the tread surface, maintaining contact with the road for improved wet and light snow traction.
- Zigzag-shaped grooves (Inner Tread) efficiently evacuates slush and snow for enhanced winter performance.
- High-density sipes throughout the tread surface, these small slits provide additional biting edges for improved wet traction.
- Applications to fit wheels with diameters ranging from 16 inches to 24 inches.





WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	EV READY
16"	215/65R16	98 V	VPCGASP127	6 1/2J	6.0-7.5	27.01	8.70	9.7	BLK	-
	225/55ZR16	99W XL	VPCGASP115	7J	6.0-8.0	25.75	9.17	10.0	BLK	-
	225/60R16	102 V XL	VPCGASP116	6 1/2J	6.0-8.0	26.61	8.98	10.0	BLK	-
	225/65R16	100 H	VPCGASP117	6 1/2J	6.0-8.0	27.48	8.98	10.0	BLK	-
	235/65R16	103 H	VPCGASP120	7J	6.5-8.5	28.03	9.45	10.0	BLK	-
17"	205/40ZR17	84W XL	VPCGASP65	7 1/2J	7.0-8.0	23.46	8.35	9.7	BLK	-
	205/45ZR17	88W XL	VPCGASP66	7J	6.5-7.5	24.25	8.11	9.7	BLK	-
	205/50R17	93V XL	VPCGASP01	6 1/2J	5.5-7.5	25.12	8.43	10.0	BLK	-
	205/55ZR17	95W XL	VPCGASP137	6 1/2J	5.5-7.5	25.91	8.43	10.0	BLK	-
	215/45R17	91V XL	VPCGASP03	7J	7.0-8.0	24.65	8.39	10.0	BLK	-
	215/50R17	91V	VPCGASP04	7J	6.0-7.5	25.51	8.90	10.0	BLK	-
	215/55R17	94V	VPCGASP05	7J	6.0-7.5	26.30	8.90	10.0	BLK	-
	215/60R17	100V XL	VPCGASP113	6 1/2J	6.0-7.5	27.17	8.70	9.7	BLK	-
	225/45ZR17	94W XL	VPCGASP08	7 1/2J	7.0-8.5	24.96	8.86	10.0	BLK	-
	225/50R17	94V	VPCGASP11	7J	6.0-8.0	25.90	9.17	10.0	BLK	-
	225/55R17	101V XL	VPCGASP12	7J	6.0-8.0	26.77	9.17	10.0	BLK	-
	235/45R17	97V XL	VPCGASP15	8J	7.5-9.0	25.35	9.29	10.0	BLK	-
	235/50R17	96V	VPCGASP18	7 1/2J	6.5-8.5	26.30	9.65	10.0	BLK	-
	235/55ZR17	103W XL	VPCGASP96	7 1/2J	6.5-8.5	27.17	9.65	10.0	BLK	-
	235/60R17	102 V	VPCGASP119	7J	6.5-8.5	28.11	9.45	10.0	BLK	-
	245/40ZR17	95Y XL	VPCGASP70	8 1/2J	8.0-9.5	24.72	9.76	9.7	BLK	-
	245/45ZR17	99Y XL	VPCGASP41	8J	8.0-9.5	25.67	9.57	10.0	BLK	-
	245/50ZR17	99 Y	VPCGASP121	7 1/2J	7.0-8.5	26.69	9.96	10.0	BLK	-
18"	215/45ZR18	89W	VPCGASP138	7J	7.0-8.0	25.63	8.39	10.0	BLK	-
	215/55R18	99V XL	VPCGASP91	7J	6.0-7.5	27.28	8.90	10.0	BLK	-
	225/40ZR18	92W XL	VPCGASP06	8J	7.5-9.0	25.08	9.06	10.0	BLK	-
	225/45ZR18	95W XL	VPCGASP09	7 1/2J	7.0-8.5	25.94	8.86	10.0	BLK	-
	225/50ZR18	99W XL	VPCGASP92	7J	6.0-8.0	26.89	9.17	10.0	BLK	-
	225/55ZR18	102W XL	VPCGASP93	7J	6.0-8.0	27.76	9.17	10.0	BLK	-
	225/60ZR18	104W XL	VPCGASP94	6 1/2J	6.0-8.0	28.62	8.98	10.0	BLK	-

WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	EV READY
18"	235/40ZR18	95W XL	VPCGASP14	8 1/2J	8.0-9.5	25.39	9.49	10.0	BLK	-
	235/45ZR18	94W	VPCGASP16	8J	7.5-9.0	26.34	9.29	10.0	BLK	-
	235/50ZR18	101W XL	VPCGASP19	7 1/2J	6.5-8.5	27.28	9.65	10.0	BLK	-
	235/55R18	104V XL	VPCGASP20	7 1/2J	6.5-8.5	28.15	9.65	10.0	BLK	-
	245/40ZR18	97W XL	VPCGASP23	8 1/2J	8.0-9.5	25.71	9.76	10.0	BLK	-
	245/45R18	100V XL	VPCGASP26	8J	7.5-9.0	26.65	9.57	10.0	BLK	-
	245/50ZR18	100 W	VPCGASP97	7 1/2J	7.0-8.5	27.68	9.96	10.0	BLK	-
	245/55ZR18	103 W	VPCGASP71	7 1/2J	7.0-8.5	28.62	9.96	10.0	BLK	-
	255/35ZR18	94W XL	VPCGASP43	9J	8.5-10.0	25.00	10.24	10.0	BLK	-
	255/40ZR18	99W XL	VPCGASP48	9J	8.5-10.0	26.02	10.24	10.0	BLK	-
	255/55ZR18	109W XL	VPCGASP49	8J	7.0-9.0	26.89	8.43	10.0	BLK	-
	255/60R18	112H XL	VPCGASP77	7 1/2J	7.0-9.0	30.04	10.24	10.0	BLK	-
	265/35ZR18	97W XL	VPCGASP79	9 1/2J	9.0-10.5	25.31	10.67	10.0	BLK	-
	275/35ZR18	99W XL	VPCGASP83	9 1/2J	9.0-11.0	25.55	10.94	10.0	BLK	-
19"	ST255/55R18	10PR 113/109Q	VPASPST1	8J	7.0-9.0	29.02	10.43	10.0	BLK	-
	225/40ZR19	93W XL	VPCGASP07	8J	7.5-9.0	26.10	9.06	10.0	BLK	-
	225/45ZR19	96W XL	VPCGASP10	7 1/2J	7.0-8.5	26.97	8.86	10.0	BLK	-
	235/35ZR19	91W XL	VPCGASP39	8 1/2J	8.0-9.5	25.47	9.49	10.0	BLK	-
	235/40R19	96V XL	VPCGASP13	8 1/2J	8.0-9.5	26.42	9.49	10.0	BLK	-
	235/45ZR19	95W	VPCGASP17	8J	7.5-9.0	27.36	9.29	10.0	BLK	-
	235/50ZR19	103W XL	VPCGASP67	7 1/2J	6.5-8.5	28.31	9.65	9.7	BLK	-
	245/35ZR19	93W XL	VPCGASP21	8 1/2J	8.0-9.5	25.79	9.76	10.0	BLK	-
	245/40ZR19	94W	VPCGASP24	8 1/2J	8.0-9.5	26.73	9.76	10.0	BLK	-
	245/45ZR19	98W	VPCGASP27	8J	7.5-9.0	27.68	9.57	10.0	BLK	-
	255/35ZR19	96YXL	VPCGASP72	9J	8.5-10.0	26.02	10.24	10.0	BLK	-
	255/40ZR19	100W XL	VPCGASP45	9J	8.5-10.0	27.05	10.24	10.0	BLK	-
	255/45ZR19 EV	104Y XL	VPCGASP99	8 1/2J	8.0-9.5	28.07	10.04	10.0	BLK	EV READY
	255/50ZR19	107Y XL	VPCGASP100	8J	7.0-9.0	29.09	10.43	10.0	BLK	-
	255/55ZR19	111W XL	VPCGASP75	8J	7.0-9.0	30.04	10.43	10.0	BLK	-
	255/60R19	113V XL	VPCGASP78	7 1/2J	7.0-9.0	31.06	10.24	10.0	BLK	-





WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	EV READY
19"	265/50ZR19	110W XL	VPCGASP102	8 1/2J	7.5-9.5	29.49	10.91	10.0	BLK	-
	275/30ZR19	96Y XL	VPCGASP51	9 1/2J	9.0-10.0	25.55	10.94	10.0	BLK	-
	285/40ZR19	103 Y	VPCGASP87	10J	9.5-11.0	27.99	11.42	10.0	BLK	-
	295/45ZR19	113Y XL	VPCGASP89	10J	9.5-11.0	29.49	11.65	10.0	BLK	-
	305/30ZR19	102Y XL	VPCGASP58	11J	10.5-11.5	26.26	12.32	10.0	BLK	-
20"	225/35ZR20	90W XL	VPCGASP114	8J	7.5-9.0	26.22	9.06	9.7	BLK	-
	235/45ZR20	100W XL	VPCGASP118	8J	7.5-9.0	28.35	9.29	9.7	BLK	-
	235/50ZR20	104Y XL	VPCGASP68	7 1/2J	6.5-8.5	29.29	9.65	9.7	BLK	-
	245/35ZR20	95W XL	VPCGASP22	8 1/2J	8.0-9.5	26.77	9.76	10.0	BLK	-
	245/40ZR20	99W XL	VPCGASP25	8 1/2J	8.0-9.5	27.72	9.76	10.0	BLK	-
	245/45ZR20	103W XL	VPCGASP28	8J	7.5-9.0	28.66	9.57	10.0	BLK	-
	245/60R20	107 H	VPCGASP98	7J	7.0-8.5	31.57	9.76	10.0	BLK	-
	255/35ZR20	97W XL	VPCGASP73	9J	8.5-10.0	27.01	10.24	10.0	BLK	-
	255/40ZR20 EV	101W XL	VPCGASP46	9J	8.5-10.0	28.03	10.24	10.0	BLK	EV READY
	255/45ZR20 EV	105W XL	VPCGASP74	8 1/2J	8.0-9.5	29.06	10.04	10.0	BLK	EV READY
	255/50ZR20	109W XL	VPCGASP101	8J	7.0-9.0	30.08	10.43	10.0	BLK	-
	255/55ZR20	110W XL	VPCGASP76	8J	7.0-9.0	31.02	10.43	10.0	BLK	-
	275/40ZR20	106W XL	VPCGASP32	9 1/2J	9.0-11.0	28.66	10.94	10.0	BLK	-
	275/50ZR20	113Y XL	VPCGASP85	8 1/2J	7.5-9.5	30.87	11.18	10.0	BLK	-
	315/35ZR20	110W XL	VPCGASP37	11J	10.5-12.5	28.66	12.60	10.0	BLK	-
	325/35ZR20	108Y	VPCGASP63	11 1/2J	11.0-13.0	28.98	13.03	10.0	BLK	-
	335/30ZR20	108Y XL	VPCGASP107	12J	11.5-12.5	27.95	13.50	10.0	BLK	-
	235/50R21	101V	VPCGASP95	7 1/2J	6.5-8.5	30.28	9.65	9.7	BLK	-
	245/35ZR21 EV	96Y XL	VPCGASP69	8 1/2J	8.0-9.5	27.76	9.76	10.0	BLK	EV READY
	245/40ZR21	100Y XL	VPCGASP40	8 1/2J	8.0-9.5	28.70	9.76	10.0	BLK	-
21"	255/30ZR21	93W XL	VPCGASP42	9J	8.5-9.5	27.05	10.24	10.0	BLK	-
	255/35ZR21 EV	98W XL	VPCGASP44	9J	8.5-10.0	27.99	10.24	10.0	BLK	EV READY
	255/40ZR21	101Y XL	VPCGASP47	9J	8.5-10.0	29.02	10.24	10.0	BLK	-
	265/35ZR21 EV	101Y XL	VPCGASP80	9 1/2J	9.0-10.5	28.31	10.67	10.0	BLK	EV READY
	265/40ZR21	105Y XL	VPCGASP81	9 1/2J	9.0-10.5	29.33	10.67	10.0	BLK	-

WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	EV READY
21"	265/45ZR21	108Y XL	VPCGASP82	9J	8.5-10.0	30.35	10.47	10.0	BLK	-
	275/30ZR21	98Y XL	VPCGASP52	9 1/2J	9.0-10.0	27.52	10.94	10.0	BLK	-
	275/35ZR21 EV	103Y XL	VPCGASP53	9 1/2J	9.0-11.0	28.54	10.94	10.0	BLK	EV READY
	275/45ZR21	110Y XL	VPCGASP84	9J	8.5-10.5	30.75	10.75	10.0	BLK	-
	285/40ZR21	109Y XL	VPCGASP55	10J	9.5-11.0	29.96	11.89	10.0	BLK	-
	295/35ZR21	107Y XL	VPCGASP88	10 1/2J	10.0-11.5	29.09	11.85	10.0	BLK	-
	295/40ZR21	111Y XL	VPCGASP57	10 1/2J	10.0-11.5	30.28	11.85	10.0	BLK	-
	315/30ZR21	105Y XL	VPCGASP59	11J	10.5-11.5	28.46	12.60	10.0	BLK	-
	315/35ZR21	111Y XL	VPCGASP60	11J	10.5-12.5	29.65	12.60	10.0	BLK	-
	315/40ZR21	115W XL	VPCGASP104	11J	10.5-12.5	30.91	12.60	10.0	BLK	-
	325/25ZR21	102Y XL	VPCGASP105	12J	11.5-12.5	27.36	13.23	10.0	BLK	-
	325/30ZR21	108Y XL	VPCGASP61	11 1/2J	11.0-12.0	28.70	13.03	10.0	BLK	-
22"	265/35R22	102V XL	VPCGASP30	9 1/2J	9.0-10.5	29.33	10.67	10.0	BLK	-
	265/50R22	112V XL	VPCGASP50	8 1/2J	7.5-9.5	32.48	10.91	10.0	BLK	-
	285/30ZR22	101Y XL	VPCGASP54	10J	9.5-10.5	28.78	11.42	10.0	BLK	-
	285/45R22	114V XL	VPCGASP33	9 1/2J	9.0-10.5	32.09	11.22	10.0	BLK	-
	305/25ZR22	99Y XL	VPCGASP103	11J	10.5-11.5	27.99	12.32	10.0	BLK	-
	305/40R22	114V XL	VPCGASP35	11J	10.0-12.0	31.61	12.32	10.0	BLK	-
	305/45R22	118V XL	VPCGASP36	10J	9.5-11.5	32.80	11.93	10.0	BLK	-
	315/35ZR22	111Y XL	VPCGASP90	11J	10.5-12.5	30.67	12.60	10.0	BLK	-
	335/25ZR22	105W XL	VPCGASP106	12J	11.5-12.5	28.62	13.50	10.0	BLK	-
23"	285/35ZR23	107Y XL	VPCGASP86	10J	9.5-11.0	30.87	11.42	10.0	BLK	-
	285/40ZR23	107Y	VPCGASP56	10J	9.5-11.0	31.97	11.42	10.0	BLK	-
	325/30ZR23	109Y	VPCGASP62	11 1/2J	11.0-12.0	30.71	13.03	10.0	BLK	-
	325/35ZR23	111Y	VPCGASP64	11 1/2J	11.0-13.0	31.97	13.03	10.0	BLK	-
24"	305/35R24	112V XL	VPCGASP34	11J	10.0-12.0	32.44	12.32	10.0	BLK	-

+ Every effort has been made to verify the accuracy of the listed specifications. Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.



COVERT GRIP CV

ALL-SEASON PERFORMANCE TIRE

The Covert Grip CV is an all-season tire designed to balance a quiet and comfortable ride with good wet and dry braking performance for passenger cars, crossovers, and SUVs. Its newly developed tread compound and optimized carcass construction promote exceptional tread wear and reduced rolling resistance.



- Solid and uniform center rib design ensures even contact pressure, enhancing braking, handling, and stability.
- Multi-directional sipes on the center rib improves traction in wet and light snow conditions.
- Locking wave sipes on outer tread blocks optimize cornering grip and handling stability.
- Variable-pitch tread design helps cancel out harmonic road noise for a quieter ride.
- Advanced tread compound is formulated to deliver exceptional tread life.
- Applications fit wheels with diameters ranging from 16 inches to 20 inches.



WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
15"	P235/75R15	105S	VPCGCV15	6 1/2J	6.0-8.0	28.86	9.25	8.9	BLK	N
	215/70R16	100H	VPCGCV02	6 1/2J	5.5-7.0	27.87	8.70	11.1	BLK	N
16"	225/70R16	103H	VPCGCV06	6 1/2J	6.0-7.5	28.43	8.98	11.1	BLK	N
	235/70R16	106H	VPCGCV14	7J	6.0-8.0	28.98	9.45	11.1	BLK	N
17"	215/65R17	99V	VPCGCV01	6 1/2J	6.0-7.5	28.03	8.70	11.1	BLK	N
	225/60R17	99V	VPCGCV04	6 1/2J	6.0-8.0	27.64	8.98	11.1	BLK	N
	225/65R17	102H	VPCGCV05	6 1/2J	6.0-8.0	28.50	8.98	11.1	BLK	N
	235/65R17	108V XL	VPCGCV12	7J	6.5-8.5	29.06	9.45	11.1	BLK	N
	245/65R17	111H XL	VPCGCV20	7J	7.0-8.5	29.53	9.76	11.1	BLK	N
18"	235/50R18	97V	VPCGCV07	7 1/2J	6.5-8.5	27.28	9.65	11.1	BLK	N
	235/55R18	100V	VPCGCV08	7 1/2J	6.5-8.5	28.15	9.65	11.1	BLK	N
	235/60R18	107V XL	VPCGCV11	7J	6.5-8.5	29.09	9.45	11.1	BLK	N
	235/65R18	106V	VPCGCV13	7J	6.5-8.5	30.04	9.45	11.1	BLK	N
	245/60R18	105V	VPCGCV19	7J	7.0-8.5	29.57	9.76	11.1	BLK	N
	255/65R18	111H	VPCGCV22	7 1/2J	7.0-9.0	31.06	10.24	11.1	BLK	N
	265/60R18	110T	VPCGCV24	8J	7.5-9.5	30.51	10.71	11.1	BLK	N
19"	225/55R19	99V	VPCGCV03	7J	6.0-8.0	28.78	9.17	11.1	BLK	N
	235/55R19	105V XL	VPCGCV09	7 1/2J	6.5-8.5	29.17	9.65	11.1	BLK	N
	245/45R19	102V XL	VPCGCV16	8J	7.5-9.0	27.68	9.57	11.1	BLK	N
	245/55R19	103V	VPCGCV18	7 1/2J	7.0-8.5	29.65	9.96	11.1	BLK	N
20"	235/55R20	102V	VPCGCV10	7 1/2J	6.5-8.5	30.16	9.65	11.1	BLK	N
	245/50R20	102V	VPCGCV17	7 1/2J	7.0-8.5	29.69	9.96	11.1	BLK	N
	255/50R20	109V XL	VPCGCV21	8J	7.0-9.0	30.08	10.43	11.1	BLK	N
	265/50R20	111V XL	VPCGCV23	8 1/2J	7.5-9.5	30.47	10.91	11.1	BLK	N
22"	275/50R22	111H	VPCGCV25	8 1/2J	7.5-9.5	32.87	11.18	11.1	BLK	N

† Every effort has been made to verify the accuracy of the listed specifications. Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.



COVERT GRIP H/T

ALL-SEASON HIGHWAY-TERRAIN FOR MODERN TRUCKS AND SUVS

The Venom Power Covert Grip H/T is an all-season highway terrain tire designed for year-round performance on modern light trucks and SUVs. It prioritizes a smooth, comfortable ride and long tread life, while maintaining excellent wet traction and handling, making it a great choice for drivers who demand all-weather capability without sacrificing comfort.



- Reinforced construction enhances handling and increases load capacity (refer to the tire's load rating for details).
- Low-rolling-resistance tread compound promotes even wear and extends the tire's lifespan.
- Waved shoulder sipes and wide grooves efficiently channel water away from the contact patch, improving wet braking and hydroplaning resistance.
- Variable-pitch tread design minimizes road noise on the three center ribs for a quieter, more comfortable ride.
- Offered in a wide range of 30 P-Metric/LT-Metric sizes, covering 16-inch to 20-inch wheel diameters. This ensures you can find the right fit for your vehicle. Additionally, it comes backed by a manufacturer's limited warranty of 50,000 miles.

ROAD HAZARD


4 YEARS WARRANTY

50K MILEAGE WARRANTY

FULL TREAD DEPTH

WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
16"	235/65R16C	10PR 121/119R	VPCGHT11	7J	6.5-7.5	28.03	9.45	13.0	BLK	N
	255/70R16	111T	VPCGHT02	7 1/2J	6.5-8.5	30.08	10.24	12.2	RWL	N
	265/70R16	112T	VPCGHT03	8J	7.0-9.0	30.63	10.71	12.2	RWL	N
	LT215/85R16	10PR 115/112Q	VPCGHT12	6J	5.5-7.0	30.39	8.50	14.0	BLK	N
	LT225/75R16	10PR 115/112R	VPCGHT13	6J	6.0-7.5	29.29	8.78	14.0	BLK	N
	LT235/85R16	10PR 120/116Q	VPCGHT14	6 1/2J	6.0-7.5	31.73	9.25	14.0	BLK	N
	LT245/75R16	10PR 120/116R	VPCGHT15	7J	6.5-8.0	30.47	9.76	14.0	BLK	N
17"	245/70R17	110T	VPCGHT04	7J	6.5-8.0	30.55	9.76	12.2	RWL	N
	265/70R17	115T	VPCGHT05	8J	7.0-9.0	31.65	10.71	12.2	RWL	N
	LT245/70R17	10PR 119/116R	VPCGHT16	7J	6.5-8.0	30.55	9.76	14.0	BLK	N
18"	265/60R18	110T	VPCGHT06	8J	7.5-9.5	30.51	10.71	12.2	BLK	N
	275/65R18	116T	VPCGHT07	8J	7.5-9.5	32.09	10.98	12.2	BLK	N
20"	275/55R20	117T XL	VPCGHT08	8 1/2J	7.5-9.5	31.89	11.18	12.2	BLK	N
	275/60R20	115T	VPCGHT09	8J	7.5-9.5	32.99	10.98	12.2	BLK	N
22"	285/45R22	114H XL	VPCGHT10	9 1/2J	9.0-10.5	32.09	11.22	12.2	BLK	N

✦ Every effort has been made to verify the accuracy of the listed specifications. Transamerica Tire cannot be held responsible for any discrepancies and as such the information should be considered as approximate.





GRAND AM

EMBRACE THE LEGACY OF CLASSIC CARS WITH THE VENOM POWER GRAND AM TIRE. THIS GRAND TOURING TIRE DELIVERS EXCEPTIONAL DURABILITY FOR EVERYDAY DRIVING WHILE OFFERING TWO DISTINCT SIDEWALL OPTIONS TO PERFECTLY COMPLEMENT YOUR CLASSIC CAR'S LOOK.

GRAND AM

Embrace the legacy of classic cars with the Venom Power Grand Am tire. This grand touring tire delivers exceptional durability for everyday driving while offering two distinct sidewall options to perfectly complement your classic car's look:

Raised White Lettering (RWL): Capture the iconic muscle car aesthetic with bold raised white lettering on the sidewall. This design harkens back to the golden age of muscle, adding a touch of timeless style to your ride.

White Wall (WW): Reimagine the vintage grandeur of wide whitewall tires. The Venom Power Grand Am's White Wall option creates a clean, two-toned aesthetic that evokes the era of chrome and fins.

- Grand touring performance: Enjoy a smooth, comfortable, and quiet ride with excellent handling for confident cruising.
- All-season capability: Maintain traction in various weather conditions with a timeless symmetrical tread pattern featuring modern high-performance compound and four grooves that direct water away to keep you on the road year-round.
- Durable radial construction: Experience long-lasting wear and uniformity for countless miles behind the wheel.



WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
13"	155/80R13	79S	VP GAM06	4.50B	4.0-5.0	22.76	6.18	10.1	WSW	N
	175/50R13	72H	VP GAM46	5.50B	5.0-6.0	19.92	7.17	10.1	RWL	N
	175/70R13	82H	VP GAM09	5J	4.5-6.0	22.68	6.97	10.1	WSW	N
	175/80R13	86S	VP GAM11	5J	4.5-6.0	24.02	6.97	10.1	WSW	N
	185/70R13	86H	VP GAM13	5 1/2B	4.5-6.0	23.23	7.44	10.1	WSW	N
	195/55R13	80H	VP GAM49	6.00B	5.5-7.0	21.43	7.91	10.1	RWL	N
14"	215/50R13	84H	VP GAM22	7.00B	6.0-7.5	21.50	8.90	10.1	RWL	N
	175/70R14	84S	VP GAM05	5J	4.5-6.0	23.70	6.97	10.1	WSW	N
	175/75R14	86S	VP GAM10	5J	4.5-6.0	24.33	6.97	10.1	WSW	N
	185/65R14	86S	VP GAM12	5 1/2J	5.0-6.5	23.46	7.44	10.1	WSW	N
	185/75R14	89S	VP GAM14	5J	4.5-6.0	24.96	7.24	10.1	WSW	N
	195/75R14	92S	VP GAM17	5 1/2J	5.0-6.5	25.51	7.72	10.1	WSW	N
	205/70R14	94S	VP GAM18	6J	5.0-7.0	25.35	8.23	10.1	WSW	N
	205/70R14	94S	VP GAM50	6J	5.0-7.0	25.35	8.23	10.1	RWL	N
	205/75R14	95S	VP GAM20	5 1/2J	5.0-7.0	26.14	7.99	10.1	WSW	N
	215/70R14	96H	VP GAM26	6 1/2J	5.5-7.0	25.91	8.70	10.1	WSW	N
	215/70R14	96H	VP GAM42	6 1/2J	5.5-7.0	25.91	8.70	10.1	RWL	N
	215/75R14	100S	VP GAM28	6J	5.5-7.0	26.69	8.50	10.1	WSW	N
	225/70R14	99H	VP GAM31	6 1/2J	6.0-7.5	26.46	8.98	10.1	RWL	N
	235/60R14	96H	VP GAM34	7J	6.5-8.5	25.12	9.45	10.1	RWL	N
	245/50R14	93H	VP GAM52	7 1/2J	7.0-8.5	23.67	9.96	10.1	RWL	N
	245/60R14	99H	VP GAM38	7J	7.0-8.5	25.59	9.76	10.1	RWL	N
15"	265/50R14	98H	VP GAM53	8 1/2J	7.5-9.5	24.46	10.91	10.1	RWL	N
	155R15	82S	VP GAM08	4 1/2J	4.0-5.0	24.80	6.18	9.1	WSW	N
	155R15	82S	VP GAM61	4 1/2J	4.0-5.0	24.80	6.18	9.1	RWL	N
	155R15	82S	VP GAM62	4 1/2J	4.0-5.0	24.80	6.18	9.1	BLK	N
	165R15	86H	VP GAM07	4 1/2J	4.0-5.0	25.43	6.57	9.1	WSW	N





WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
15"	185R15	93S	VPGAM47	5 1/2J	4.5-6.0	26.54	7.40	9.1	WSW	N
	155/80R15	83S	VPGAM63	4 1/2J	4.0-5.0	24.76	6.18	9.1	WSW	N
	155/80R15	83S	VPGAM64	4 1/2J	4.0-5.0	24.76	6.18	9.1	RWL	N
	155/80R15	83S	VPGAM65	4 1/2J	4.0-5.0	24.76	6.18	9.1	BLK	N
	185/70R15	89H	VPGAM48	5 1/2J	4.5-6.0	25.24	7.44	10.1	WSW	N
	195/60R15	88S	VPGAM15	6J	5.5-7.0	24.21	7.91	10.1	WSW	N
	195/65R15	91S	VPGAM16	6J	5.5-7.0	25.00	7.91	10.1	WSW	N
	205/70R15	96S	VPGAM19	6J	5.0-7.0	26.34	8.23	10.1	WSW	N
	205/75R15	97S	VPGAM21	5 1/2J	5.0-7.0	27.13	7.99	10.1	WSW	N
	215/60R15	94H	VPGAM23	6 1/2J	6.0-7.5	25.16	8.70	10.1	RWL	N
	215/65R15	96H	VPGAM25	6 1/2J	6.0-7.5	26.02	8.70	10.1	RWL	N
	215/70R15	98S	VPGAM27	6 1/2J	5.5-7.0	26.89	8.70	10.1	WSW	N
	215/70R15	98S	VPGAM43	6 1/2J	5.5-7.0	26.89	8.70	10.1	RWL	N
	215/75R15	100S	VPGAM29	6J	5.5-7.0	27.68	8.50	10.1	WSW	N
	225/60R15	96H	VPGAM45	6 1/2J	6.0-8.0	25.63	8.98	10.1	RWL	N
	225/70R15	100S	VPGAM32	6 1/2J	6.0-7.5	26.73	8.98	10.1	WSW	N
	225/70R15	100S	VPGAM44	6 1/2J	6.0-7.5	26.73	8.98	10.1	RWL	N
	225/75R15	102S	VPGAM33	6J	6.0-7.5	28.31	8.78	10.1	WSW	N
	235/60R15	98V	VPGAM35	7J	6.5-8.5	26.10	9.45	10.1	RWL	N
	235/70R15	106T XL	VPGAM04	7J	6.0-8.0	27.99	9.45	10.1	RWL	N
	235/70R15	102S	VPGAM36	7J	6.0-8.0	27.99	9.45	10.1	WSW	N
	235/75R15	105S	VPGAM37	6 1/2J	6.0-8.0	28.86	9.25	10.1	WSW	N
	245/60R15	101V	VPGAM39	7J	7.0-8.5	26.57	9.76	10.1	RWL	N
	255/60R15	102V	VPGAM40	7 1/2J	7.0-9.0	27.05	10.24	10.1	RWL	N
	255/70R15	112T XL	VPGAM03	7 1/2J	6.5-8.5	29.09	10.24	10.1	RWL	N
	265/50R15	99H	VPGAM41	8 1/2J	7.5-9.5	25.47	10.91	10.1	RWL	N
	275/60R15	107T	VPGAM02	8J	7.5-9.5	27.99	10.98	10.1	RWL	N
	295/50R15	108S	VPGAM01	9 1/2J	8.0-10.5	26.65	12.17	10.1	RWL	N
16"	215/60R16	95S	VPGAM24	6 1/2J	6.0-7.5	26.14	8.70	10.1	WSW	N
	225/60R16	98S	VPGAM30	6 1/2J	6.0-8.0	26.61	8.98	10.1	WSW	N

✦ Every effort has been made to verify the accuracy of the listed specifications. Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.



Van-Co ALLSeason

ALL-SEASON COMMERCIAL VAN TIRE

Built to handle the demanding workloads of commercial vans, the all-position Van-Co ALLSeason tires deliver exceptional mileage and durability for applications like delivery hauling, passenger transportation, and other commercial uses. The commercial-grade construction enhances tread life and withstands the rigors of everyday use. In addition, the all-season tread design provides confident handling on dry and wet road roads.



- Durable construction minimizes downtime with a robust construction designed for commercial applications.
- Long-wearing tread compound engineered to resist wear and tear on city and residential streets.
- Three deep circumferential grooves efficiently channel water and slush away from the tread, improving hydroplaning resistance.
- Wide tread blocks and a closed shoulder design ensure confident handling and stability, even when fully loaded.
- Sipes throughout the tread provide biting edges for all-weather grip, including wet and light snow conditions, for enhanced braking performance.
- Deep tread depth delivers extended service life, reducing tire replacement frequency.



WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
16"	195/75R16C	10PR 112/110R	TVPVANC02	5.5J	5.00-6.00	27.48	7.72	11.4	BLK	Y
	235/65R16C	12PR 122/120R	TVPVANC01	7J	6.50-7.50	28.03	9.44	11.4	BLK	Y

† Every effort has been made to verify the accuracy of the listed specifications. Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.

AT-Co ALLSeason

HEAVY-DUTY ALL-TERRAIN COMMERCIAL TIRE

The Venom Power AT-Co ALLSeason is a drive-position heavy-duty all-terrain tire built for commercial vehicles' most challenging jobs in all-weather and off-road terrain conditions. Designed for long service life, on-road stability, durability, and enhanced off-road traction on rain, mud, and snow, the Venom Power AT-Co ALLSeason provides heavy-duty truck owners with dependable year-round performance.



- Unique drive-position tread pattern that can also be used as an all-position tire for versatility.
- Durable tread compound designed to resist irregular wear and tear from scrubbing.
- Siped tread blocks for increased wet and snow traction and shorter braking distances in all-season conditions.
- Three circumferential grooves for enhanced water and slush evacuation to reduce the risk of hydroplaning.
- Aggressive all-terrain lug design and deep tread blocks for improved handling on rough terrain.
- Deep tread depth to provide long tire life and reduce replacement frequency.
- Three-Peak Mountain Snowflake (3PMSF) rated for severe snow service conditions, providing year-round confidence.



WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
19.5"	225/70R19.5	14PR 128/126 M	TVPATC01	6.75	6.00-6.75	31.93	8.90	19.0	BLK	Y
	245/70R19.5	16PR 135/133 M	TVPATC02	7.50	6.75-7.50	33.03	9.76	19.0	BLK	Y

✦ Every effort has been made to verify the accuracy of the listed specifications. Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.

LIGHT TRUCK & PASSENGER CAR TIRE

LIMITED WARRANTY

STANDARD COVERAGE

If your VENOM POWER tire becomes unserviceable as a result of an eligible adjustable condition during the first 10% of tread life, the owner will be compensated 100% of the value of the tire. After that amount, VENOM POWER will offer a prorated mileage credit, down to 25% remaining tread depth, towards purchasing a comparable VENOM POWER brand tire. The owner must pay for mounting, balancing, and any other additional charges, such as taxes and freight. VENOM POWER shall not be responsible for any other fees incurred as a part of any exchange, labor, or additional costs resulting from this guarantee. VENOM POWER shall not be responsible for any damage or other issues caused by the improper installation (including any of the exclusions below), balancing, or selection of tire—including the selection of size, specification, type, or use of such tire (including those obligations under the “Owner’s Obligations section below”) that the manufacturer of your vehicle does not recommend. All terms and conditions of this guarantee are limited to the terms and conditions contained in this guarantee.

VENOM POWER tires include the Standard Coverage and the additional coverages listed below.

MILEAGE WARRANTY

- 50,000 miles tread life warranty for Terra Hunter X/T, X/T2, R/T, and R/T+ 22-inch and smaller sizes, and 13.5-inch wide or less.
- 50,000 miles tread life warranty for Trail Hunter R/T 22-inch and smaller sizes, and 13.5-inch wide or less.
- 55,000 miles tread life warranty for Swampthing A/T 22-inch and smaller sizes, and 13.5-inch wide or less.
- 50,000 miles tread life warranty for Ragnarok GTS UHP 35-series and above aspect ratio and 22-inch and below sizes.
- **50,000 miles tread life warranty for COVERT GRIP ASP, COVERT GRIP CV, COVERT GRIP H/T**
- Vehicles with staggered fitments, where the front and rear tires have different tire sizes, cannot be rotated. VENOM POWER warrants tires mounted on the rear axle of vehicles with staggered fitments only up to 50% of the warranted miles under our standard mileage warranty for specific tire models, tread patterns, and tire sizes.

VENOM POWER tires are warrantied against treadwear prior to the applicable indicated mileage for each specific tire model and size, provided that you:

1. Rotate your tires following the prescribed rotation patterns at least every 3,500 miles or less (UHP passenger car tires) or 5,000 miles or less (standard light truck tires) and have documentation showing the rotation schedule.
2. The TIRE SERVICE RECORD form filled out by the tire shop, dealer, or service department during regular routine maintenance. The required TIRE SERVICE RECORD form can be downloaded [here](#) or at the bottom of this page.
3. Present the subject tire for adjustment during regular routine maintenance.
4. Present documentation showing the rotation schedule when requesting an adjustment and the date of purchase, vehicle type, model, odometer reading, and tire pressure.

When the tread becomes worn to 2/32 inch (shown by tread wear indicators molded into the tread grooves), the tire tread shall be considered worn. The Department of Transportation specifications determine such tread wear, and in accordance with applicable laws and regulations.

4-YEAR MANUFACTURER WARRANTY

The 4-Year Manufacturer Warranty is a non-prorated replacement for any manufacturing defects in material and workmanship under normal and intended use. Non-intended uses include racing, off-road use, or competition use. If a manufacturing defect in material or workmanship occurs, the tire will be replaced at no charge, on a non-prorated basis to the consumer.

CONDITIONS AND EXCLUSIONS

VENOM POWER tire warranties are limited to the original purchaser and the original vehicle on which they are installed, and such warranties and guarantees are not assignable to subsequent purchasers or vehicles. All warranties and guarantees by VENOM POWER tires are only applicable in the United States and Canada. This warranty does not cover any tires used or equipped on a vehicle registered or operated outside the United States and Canada.

The Limited Warranty does NOT cover the following:

- Tire branded or marked “blem,” “Non-Adjustable (N/A),” or previously adjusted.
- Failure, damage, or irregular wear due to:
 - Road hazards (i.e., punctures, cuts, snags, bruises, impact breaks, etc.), wreck or collision;
 - Fire, accident, or vandalism;
 - Mechanical condition of the vehicle, including misalignment, wheel imbalance, faulty shocks or brakes;
 - Misapplication of tire or use of improper inner tube;

- Alteration of the tire or addition of foreign material.
- Use of tire chains, tire spinning, racing, off-road use, or other competitive activities.
- Non-factory vehicle staggered tire fitments.
- Costs of mounting and balancing service.
- Costs related to tire pressure monitoring systems.
- Costs related to shipping and transportation of the tire.
- Loss of time or use, inconvenience, or any incidental or consequential damages.

- Improper use or operation including, but not limited to: improper tire and vehicle maintenance, running flat or run with severe underinflation, misuse, abuse, accident fire or chemical corrosion, underinflation, overinflation, overloading, over deflection, or failure to follow recommended rotation practices.
- Improper installation, improper mounting or dismounting, misapplication, improper repairs, wheel misalignment, or imbalance in the tire/wheel assembly.
- Tire size, load, and speed rating do not match the tire specifications outlined in your vehicle owner's manual.
- Tires with the Department of Transportation (DOT) number removed or rendered illegible; tires must bear the DOT prescribed tire identification numbers.
- Ride complaints after the first 1/32nd of tread wear or due to damaged wheels or any vehicle condition.

VENOM POWER Tires does not warrant any work performed by the dealer, including, but not limited to their selection, fitment, mounting and balancing, inspection, or repair of any tire.

INELIGIBLE TIRES

Tires are not eligible for warranty if:

- The mileage and tire rotation records are not available or verifiable.
- The subject tire or tires are not presented and available for inspection at an authorized dealer.
- The subject tire or tires are worn beyond the tread wear bar indicators (less than 2/32nd of remaining tread).
- Uniformity issues after the first 1/32nd of tread wear.

CONSUMER RIGHTS

This Limited Warranty gives you specific legal rights; you may also have other rights, which vary from state to state.

VENOM POWER Tires disclaims all other warranties, express or implied, including the implied warranty of merchantability, the implied warranty of fitness for a particular purpose and liability for incidental and consequential damages (i.e., loss of time, loss of use of vehicle, road services, towing charges, inconveniences, etc.).

Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above exclusions may not apply to you.

NO ONE (including a VENOM POWER Tires employee, representative, or dealer) has the authority to vary the terms of this Limited Warranty.*

OWNER'S OBLIGATION

When making a claim, you must return the tire to be replaced to your VENOM POWER tire dealer and sign the customer signature section of the VENOM POWER Tire Claim Form.

Proper vehicle and tire care are necessary to obtain the expected wear from a tire. Therefore, it is your obligation to properly maintain your tires and the vehicle upon which they are mounted, including:

1. Operating your tires at the inflation pressures recommended by the tire and vehicle manufacturer.
2. Keeping your tire and wheel assemblies in balance.
3. Proper wheel alignment.
4. Maintaining steering and suspension components to be within manufacturer specifications.
5. Rotating your tires at least every 3,500 miles or less (UHP passenger car tires) or 5,000 miles or less (standard light truck tires).

We recommend that you have your VENOM POWER tire dealer inspect your tires any time you notice irregular or uneven tread wear and rotate them, if necessary.

Failure to follow any of the above-mentioned Owner Obligations may be considered a breach of the warranty agreement and result in the termination of the warranty agreement. Furthermore, VENOM POWER reserves the right to review each warranty claim and deny the warranty application based on failing to follow any of the above-mentioned Owner Obligations.

* VENOM POWER reserves the right to change the terms and conditions of all warranties at any time.

CLAIMS PROCESS

To make a claim under this Limited Warranty, you must:

1. Present your vehicle with the subject tires, the original copy of this Limited Warranty and the original sales invoice to an authorized VENOM POWER dealer.
2. Present your completed Tire Service Record to the authorized VENOM POWER dealer along with the other two documents in #1. For treadwear mileage warranty consideration, the Tire Service Record must show the times and places that the tire rotations were performed. VENOM POWER recommends rotations at 3,500-mile intervals or less for high-performance passenger car tires and 5,000-mile intervals or less for standard light truck tires.
3. Complete and sign the VENOM POWER Limited Warranty Claim form provided by the dealer, keep a copy for your records, and leave the tire with the dealer.
4. If you purchased the tire from an Internet or mail-order merchant, you will need to submit your claim, together with the dismounted tire, to that merchant. You are responsible for all of the costs of dismounting and shipping. Your claim will be administered in accordance with the Limited Warranty that was in effect when you purchased the tires.

FORMS (available for download on www.venompowertires.com)

Limited Warranty
Tire Service Record
Limited Warranty Claim Form

CONTACT INFORMATION

VENOM POWER TIRE
5118 Park Avenue, Suite 601
Memphis, TN 38117





Built for Adventure



TRAIL HUNTER R/T

ON- AND OFF-ROAD MAX TRACTION
RUGGED-TERRAIN TIRE



TRAIL HUNTER ATX

ON- AND OFF-ROAD MAX TRACTION ALL-TERRAIN TIRE



TRAIL HUNTER ATS

ALL-TERRAIN PERFORMANCE TIRE
FOR CROSSOVERS AND LIGHT TRUCKS



COVERT GRIP CV

ALL-SEASON PERFORMANCE TIRE



COVERT GRIP H/T

ALL-SEASON HIGHWAY-TERRAIN
FOR MODERN TRUCKS AND SUVs



GRAND AM

RAISED WHITE LETTERING (RWL)



RAGNAROK GT S

ALL-SEASON HIGH PERFORMANCE TIRE



ICE HUNTER WT S

LIGHT TRUCK WINTER TIRE



COVERT GRIP ASP

ALL-SEASON ULTRA-HIGH-PERFORMANCE (UHP)



GRAND AM

WHITE WALL (WW)



Van-Co AllSeason

ALL-SEASON COMMERCIAL VAN TIRE



AT-Co AllSeason

HEAVY-DUTY ALL-TERRAIN COMMERCIAL TIRE