TRANSAMERICA TIRE CO.,LTD.
5118 PARK AVE., SUITE 601, MEMPHIS, TN 38117
832-891-2821 | MARKETING@TRANSAMERICATIRE.COM
@VENOMPOWERTIRES
WWW.VENOMPOWERTIRES.COM

SWAMPTHING

MAXIMUM TRACTION ALL-TERRAIN TIRE

MAXIMUM TRACTION MUD-TERRAIN TIRE

VENOM® POWER

Built for Adventure



SWAMPTHING MIT

MAXIMUM TRACTION MUD-TERRAIN TIRE

WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
14"	27X8.50R14LT	6PR 95Q	CVPSWMT25	7J	5.5-7.0	26.52	8.58	16.0	BLK	N
15"	30X9.50R15LT	6PR 104Q	CVPSWMT40R	7 1/2J	6.0-8.0	29.52	9.46	19.0	RWL	N
16"	LT265/75R16	10PR 123/120Q	CVPSWMT21	7 1/2J	7.0-9.0	31.65	10.51	19.0	BLK	N
	LT285/75R16	126/123Q	CVPSWMT23	8J	7.5-9.5	32.83	11.26	19.0	BLK	N
17"	LT265/70R17	10PR 123/120Q	CVPSWMT19	8J	7.0-9.0	31.65	10.71	19.0	RWL	N
	LT285/70R17	10PR 126/123Q	CVPSWMT20	8 1/2J	7.5-9.5	32.76	11.50	19.0	RWL	N
	LT315/70R17	10PR 126/123Q	CVPSWMT18	9 1/2J	8.0-10.5	34.41	12.72	21.0	BLK	N
	35X12.50R17LT	12PR 128R	CVPSWMT01	10J	8.0-10.5	34.52	12.50	21.0	BLK	N
	37X12.50R17LT	8PR 124Q	CVPSWMT28R	10J	8.0-10.5	36.52	12.50	21.0	RWL	N
	37X12.50R17LT	10PR 128Q	CVPSWMT29R	10J	8.0-10.5	36.52	12.50	21.0	RWL	N
	37X13.50R17LT	10PR 128Q	CVPSWMT17	11J	9.0-11.5	36.52	13.58	21.0	BLK	N
	40x13.50R17LT	8PR 128Q	CVPSWMT35	11J	9.0-11.5	39.52	13.58	21.0	BLK	N
18"	35X12.50R18LT	12PR 128R	CVPSWMT02	10J	8.5-11.0	34.52	12.50	21.0	BLK	N
20"	33X12.50R20LT	10PR 114Q	CVPSWMT03	10J	8.5-11.0	32.52	12.50	21.0	BLK	N
	33X12.50R20LT	12PR 119Q	CVPSWMT04	10J	8.5-11.0	32.52	12.50	21.0	BLK	N
	35X12.50R20LT	10PR 121Q	CVPSWMT05	10J	8.5-11.0	34.52	12.50	21.0	BLK	N
	35X12.50R20LT	12PR 125Q	CVPSWMT06	10J	8.5-11.0	34.52	12.50	21.0	BLK	N
	35X15.50R20LT	12PR 127Q	CVPSWMT37R	12 1/2J	11.0-14.0	34.52	15.54	21.0	RWL	N
	38X13.50R20LT	10PR 128Q	CVPSWMT24	11J	9.5-12.0	37.52	13.58	21.0	BLK	N
	40x13.50R20LT	10PR 128Q	CVPSWMT26	11J	9.0-11.5	39.52	13.58	21.0	BLK	N
22"	33X12.50R22LT	10PR 109Q	CVPSWMT09	10J	10.0-12.0	32.52	12.45	21.0	BLK	N
	33X12.50R22LT	12PR 114Q	CVPSWMT10	10J	10.0-12.0	32.52	12.45	21.0	BLK	N
	33X13.50R22LT	12PR 116Q	CVPSWMT30	12J	11.5-12.5	32.52	13.58	21.0	BLK	N
	35X12.50R22LT	10PR 117Q	CVPSWMT11	10J	8.5-11.0	34.52	12.50	21.0	BLK	N
	35X12.50R22LT	12PR 121Q	CVPSWMT12	10J	8.5-11.0	34.52	12.50	21.0	BLK	N
	35X13.50R22LT	12PR 122Q	CVPSWMT31	11J	10.5-12.0	34.52	13.58	21.0	BLK	N
	35X15.50R22LT	12PR 123Q	CVPSWMT38	13J	12.5-14.5	34.52	15.43	21.0	BLK	N
24"	35X15.50R24LT	12PR 117Q	CVPSWMT39	14J	13.0-15.5	34.52	15.52	21.0	BLK	N
26"	37X12.50R26LT	12PR 117Q	CVPSWMT16	10J	9.5-11.5	36.52	12.50	21.0	BLK	N
	37X13.50R26LT	12PR 117Q	CVPSWMT41	12J	11.5-13.5	36.52	13.44	21.0	BLK	N
	38X15.50R26LT	12PR 126P	CVPSWMT34	14J	13.5-14.5	37.52	15.47	21.0	BLK	N
30"	42X16.50R30LT	10PR 126Q	CVPSWMT14	15J	14.5-16.0	41.54	16.57	21.0	BLK	N
	44X16.50R30LT	10PR 128Q	CVPSWMT15	15J	14.0-16.0	43.50	16.57	21.0	BLK	N

SWAMPTHING AIT

MAXIMUM TRACTION ALL-TERRAIN TIRE

WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM CONTOURS	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
15"	205/70R15	100T XL	TVPSWAT69	6J	5.0-7.0	26.34	8.23	13.6	BLK	Y
16"	215/70R16	100T	TVPSWAT66	6 1/2J	5.5-7.0	27.87	8.70	13.6	BLK	Y
	LT305/70R16	12PR 128/125R	TVPSWAT51	9J	8.0-10.0	32.83	12.24	16.0	RWL	N
	LT315/75R16	10PR 127/124R	TVPSWAT52	8 1/2J	8.0-10.5	34.57	12.32	16.0	RWL	N
17"	LT265/70R17	10PR 121/118Q	TVPSWAT55	8J	7.0-9.0	31.65	10.71	16.0	RWL	Y
	LT285/70R17	10PR 126/123Q	TVPSWAT56	8 1/2J	7.5-9.5	32.76	11.50	16.0	RWL	N
	LT295/70R17	10PR 128/125R	TVPSWAT50	8 1/2J	7.5-10.0	33.31	11.77	16.0	BLK	N
	LT305/70R17	10PR 125/122R	TVPSWAT53	9J	8.0-10.0	33.86	12.24	16.0	RWL	N
	LT315/70R17	10PR 126/123R	TVPSWAT47	9 1/2J	8.0-10.5	34.41	12.72	16.0	BLK	N
	35X11.50R17LT	10PR 128Q	TVPSWAT60	9J	7.5-10.0	34.52	11.42	16.0	RWL	N
	35X12.50R17LT	10PR 125Q	TVPSWAT58	10J	8.0-10.5	34.52	12.50	17.0	BLK	N
	37X11.50R17LT	8PR 128R	TVPSWAT64R	9J	7.5-10.0	36.52	11.42	17.0	RWL	N
	37X12.50R17LT	12PR 128Q	TVPSWAT34	10J	8.0-10.5	36.52	12.50	17.0	BLK	N
	37X13.50R17LT	10PR 128Q	TVPSWAT35	11J	9.0-11.5	36.52	13.58	17.0	BLK	N
18"	37X11.50R18LT	10PR 128Q	TVPSWAT65R	9J	7.5-10.0	36.52	11.42	17.0	RWL	N
	37X12.50R18LT	12PR128Q	TVPSWAT38	10J	8.0-10.5	36.52	12.50	17.0	BLK	N
	37X13.50R18LT	12PR128Q	TVPSWAT39	11J	9.5-12.0	36.52	13.58	17.0	BLK	N
20"	265/50R20	111H XL	TVPSWAT48	8 1/2J	7.5-9.5	30.47	10.91	13.6	BLK	Y
	LT275/55R20	10PR 120/117Q	TVPSWAT57	8 1/2J	8.0-9.5	31.89	11.18	16.0	BLK	Y
	LT285/55R20	10PR 122/119Q	CVPSWAT19	9J	8.5-10.0	32.36	11.69	16.0	BLK	N
	LT285/65R20	10PR 127/124Q	TVPSWAT62R	8 1/2J	8.5-10.0	34.57	11.50	16.0	RWL	N
	LT295/65R20	10PR 129/126R	TVPSWAT43	8 1/2J	8.5-10.5	35.12	11.77	16.0	BLK	N
	33X11.50R20LT	10PR 118Q	CVPSWAT20	9J	8.0-10.5	32.52	11.42	16.0	BLK	N
	33X12.50R20LT	10PR 114Q	CVPSWAT22	10J	8.5-11.0	32.52	12.50	17.0	BLK	N
	33X12.50R20LT	12PR 119Q	CVPSWAT23	10J	8.5-11.0	32.52	12.50	17.0	BLK	N
	35X11.50R20LT	10PR 124Q	TVPSWAT63R	9J	8.0-10.5	34.52	11.42	16.0	RWL	N
	35X12.50R20LT	10PR 121Q	CVPSWAT25	10J	8.5-11.0	34.52	12.50	17.0	BLK	N
	35X12.50R20LT	12PR 125Q	CVPSWAT26	10J	8.5-11.0	34.52	12.50	17.0	BLK	N
22"	HL275/50R22	116H XL	TVPSWAT68	8 1/2J	7.5-9.5	32.87	11.18	13.6	BLK	Y
	LT285/55R22	10PR 124/121S	TVPSWAT59	9J	8.5-10.0	34.37	11.69	16.0	BLK	N
	33X12.50R22LT	10PR 109Q	CVPSWAT28	10J	10.0-12.0	32.52	12.45	17.0	BLK	N
	33X12.50R22LT	12PR 114Q	CVPSWAT29	10J	10.0-12.0	32.52	12.45	17.0	BLK	N
	35X12.50R22LT	10PR 117Q	CVPSWAT31	10J	8.5-11.0	34.52	12.50	17.0	BLK	N
	35X12.50R22LT	12PR 121Q	CVPSWAT32	10J	8.5-11.0	34.52	12.50	17.0	BLK	N
24"	35X12.50R24LT	12PR 116Q	TVPSWAT46	10 1/2J	10.0-12.0	34.52	12.45	17.0	BLK	N
	35X13.50R24LT	12PR 116Q	TVPSWAT54	12J	11.5-13.5	34.52	13.44	17.0	BLK	N

VENOM POWER
Built for Adventure

* Every effort has been made to verify the accuracy of the listed Information. Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.